

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

FORM 3

AMENDED REPORT ☐
(highlight changes)

APPLICATION FOR PERMIT TO DRILL				5. MINERAL LEASE NO: ML-21835	6. SURFACE: State
1A. TYPE OF WORK: DRILL <input checked="" type="checkbox"/> REENTER <input type="checkbox"/> DEEPEN <input type="checkbox"/>				7. IF INDIAN, ALLOTTEE OR TRIBE NAME: NA	
B. TYPE OF WELL: OIL <input checked="" type="checkbox"/> GAS <input type="checkbox"/> OTHER _____ SINGLE ZONE <input checked="" type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/>				8. UNIT or CA AGREEMENT NAME: NA	
2. NAME OF OPERATOR: Newfield Production Company				9. WELL NAME and NUMBER: State 4-36-8-15	
3. ADDRESS OF OPERATOR: Route #3 Box 3630 CITY Myton STATE UT ZIP 84052			PHONE NUMBER: (435) 646-3721	10. FIELD AND POOL, OR WILDCAT: Monument Butte	
4. LOCATION OF WELL (FOOTAGES) AT SURFACE: NW/NW 615' FNL 468' FWL 569264X 40.090045 AT PROPOSED PRODUCING ZONE: 4436748Y 110.187587				11. QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: NWNW 36 8S 15E	
14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE: Approximately 12.5 miles southwest of Myton, Utah				12. COUNTY: Duchesne	13. STATE: UTAH
15. DISTANCE TO NEAREST PROPERTY OR LEASE LINE (FEET) Approx. 468' f/lse line, NA' f/unit line		16. NUMBER OF ACRES IN LEASE: 640.00 acres		17. NUMBER OF ACRES ASSIGNED TO THIS WELL: 40 acres	
18. DISTANCE TO NEAREST WELL (DRILLING, COMPLETED, OR APPLIED FOR) ON THIS LEASE (FEET) Approx. 1791'		19. PROPOSED DEPTH: 6,280		20. BOND DESCRIPTION: #B001834	
21. ELEVATIONS (SHOW WHETHER DF, RT, GR, ETC.): 5718' GL		22. APPROXIMATE DATE WORK WILL START: 3rd Qtr. 2009		23. ESTIMATED DURATION: (7) days from SPUD to rig release	

24. PROPOSED CASING AND CEMENTING PROGRAM							
SIZE OF HOLE	CASING SIZE, GRADE, AND WEIGHT PER FOOT			SETTING DEPTH	CEMENT TYPE, QUANTITY, YIELD, AND SLURRY WEIGHT		
12 1/4	8 5/8	J-55	24.0	300	Class G w/2% CaCl	155 sx +/-	1.17 15.8
7 7/8	5 1/2	J-55	15.5	6,280	Lead(Prem Lite II)	275 sx +/-	3.26 11.0
					Tail (50/50 Poz)	450 sx +/-	1.24 14.3

25. ATTACHMENTS	
VERIFY THE FOLLOWING ARE ATTACHED IN ACCORDANCE WITH THE UTAH OIL AND GAS CONSERVATION GENERAL RULES:	
<input checked="" type="checkbox"/> WELL PLAT OR MAP PREPARED BY LICENSED SURVEYOR OR ENGINEER	<input checked="" type="checkbox"/> COMPLETE DRILLING PLAN
<input checked="" type="checkbox"/> EVIDENCE OF DIVISION OF WATER RIGHTS APPROVAL FOR USE OF WATER	<input type="checkbox"/> FORM 5, IF OPERATOR IS PERSON OR COMPANY OTHER THAN THE LEASE OWNER

NAME (PLEASE PRINT) Mandie Crozier TITLE Regulatory Specialist
SIGNATURE Mandie Crozier DATE 2/27/09

(This space for State use only)

API NUMBER ASSIGNED: 43-01334231 APPROVAL: _____

RECEIVED
MAR 09 2009
DIV. OF OIL, GAS & MINING

WORKSHEET
APPLICATION FOR PERMIT TO DRILL

APD RECEIVED: 03/09/2009

API NO. ASSIGNED: 43-013-34231

WELL NAME: STATE 4-36-8-15

OPERATOR: NEWFIELD PRODUCTION (N2695)

CONTACT: MANDIE CROZIER

PHONE NUMBER: 435-646-3721

PROPOSED LOCATION:

NWNW 36 080S 150E

SURFACE: 0615 FNL 0468 FWL

BOTTOM: 0615 FNL 0468 FWL

COUNTY: DUCHESNE

LATITUDE: 40.08005 LONGITUDE: -110.18759

UTM SURF EASTINGS: 569269 NORTHINGS: 4436748

FIELD NAME: MONUMENT BUTTE (105)

INSPECT LOCATN BY: / /

Tech Review

Initials

Date

Engineering

Deo

4/23/09

Geology

Surface

LEASE TYPE: 3 - State

LEASE NUMBER: ML-21835

SURFACE OWNER: 3 - State

PROPOSED FORMATION: GRRV

COALBED METHANE WELL? NO

RECEIVED AND/OR REVIEWED:

☒ Plat
☒ Bond: Fed[] Ind[] Sta[] Fee[]
(No. Bee 1834)
☒ Potash (Y/N)
☒ Oil Shale 190-5 (B) or 190-3 or 190-13
☒ Water Permit
(No. 43-7478)
☒ RDCC Review (Y/N)
(Date: _____)
☒ Fee Surf Agreement (Y/N)
☒ Intent to Commingle (Y/N)

LOCATION AND SITING:

____ R649-2-3.
Unit: _____
☒ R649-3-2. General
Siting: 460 From Qtr/Qtr & 920' Between Wells
____ R649-3-3. Exception
____ Drilling Unit
Board Cause No: _____
Eff Date: _____
Siting: _____
____ R649-3-11. Directional Drill

COMMENTS:

Needs Permit (03-04-09)

STIPULATIONS:

*1- Specific Strip
2- STATEMENT OF BASIS
3- Surface Csg Cont Strip*

Application for Permit to Drill

Statement of Basis

3/12/2009

Utah Division of Oil, Gas and Mining

Page 1

APD No	API WellNo	Status	Well Type	Surf Ownr	CBM
1314	43-013-34231-00-00		OW	S	No
Operator	NEWFIELD PRODUCTION COMPANY	Surface Owner-APD			
Well Name	STATE 4-36-8-15	Unit			
Field	MONUMENT BUTTE	Type of Work			
Location	NWNW 36 8S 15E S 615 FNL 468 FWL	GPS Coord (UTM) 569269E 4436748N			

Geologic Statement of Basis

Newfield proposes to set 300' of surface casing at this location. The base of the moderately saline water at this location is estimated to be at a depth of 400'. A search of Division of Water Rights records shows no water wells within a 10,000 foot radius of the center of section 36. The surface formation at this site is the Uinta Formation. The Uinta Formation is made up of interbedded shales and sandstones. The sandstones are mostly lenticular and discontinuous and should not be a significant source of useable ground water. The surface casing should be extended to cover the base of the moderately saline ground water.

Brad Hill
APD Evaluator

3/12/2009
Date / Time

Surface Statement of Basis

The general location is approximately 12 road miles southwest of Myton, UT in the upper portion of the Pleasant Valley Drainage. Wells Draw is approximately 2 miles to the east and the Ute Tribal Indian Reservation 1 mile to the west. Broad flats with rolling hills characterize the area. Flats are often intersected by drainages with gentle to moderate side slopes. Flats at lower elevations to the northeast are frequently used for agriculture. No seeps, springs or streams are known to exist in the immediate area. An occasional pond for livestock watering occurs. Pleasant Valley Wash drains into the Pariette Draw drainage of Duchesne County. The lower reaches of both of these draws contain perennial streams somewhat consisting of irrigation runoff and seepage. Pariette Draw runs into the Green River approximately 6 miles downstream from Ouray, Utah and about 18 miles down drainage from the area. Access is by State and County and existing or proposed oilfield development roads to within 1280 feet of the site. From this point additional construction will be required.

The proposed State 4-36-8-15 oil well location is laid out in a southeasterly to northwesterly direction on a moderately gentle slope leading away from a ridge or rise to the west. The area slopes toward Pleasant Valley Wash. A small drainage meanders across the south part of the location. The reserve pit topsoil will divert it. Following pit closure a diversion needs to be constructed in a location determined most suitable by the operator. A culvert may be needed under the access road for this diversion. The proposed site appears to be a suitable location for constructing a pad and drilling and operating a well. It has been located in the west edge of the drilling window to better fit the terrain.

Both the surface and minerals are owned by SITLA. Ed Bonner and Jim Davis of SITLA were invited to the pre-site evaluation. Neither attended.

Pat Rainbolt and Ben Williams represented the Utah Division of Wildlife Resources. Mr. Rainbolt stated the area was classified as substantial value antelope habitat but did not recommend any restrictions for this species. No other wildlife should be significantly affected. Mr. Rainbolt gave Mr. Eaton of Newfield Production Company a copy of his written evaluation and also a UDWR seed mix recommendation to be used when the reserve pit and location are reclaimed.

Floyd Bartlett
Onsite Evaluator

3/4/2009
Date / Time

Application for Permit to Drill

Statement of Basis

3/12/2009

Utah Division of Oil, Gas and Mining

Page 2

Conditions of Approval / Application for Permit to Drill

Category	Condition
Pits	A synthetic liner with a minimum thickness of 16 mils with a felt subliner shall be properly installed and maintained in the reserve pit.
Surface	Drainages adjacent to the proposed pad shall be diverted around the location.
Surface	The reserve pit shall be fenced upon completion of drilling operations.

ON-SITE PREDRILL EVALUATION

Utah Division of Oil, Gas and Mining

Operator NEWFIELD PRODUCTION COMPANY
Well Name STATE 4-36-8-15
API Number 43-013-34231-0 **APD No** 1314 **Field/Unit** MONUMENT BUTTE
Location: 1/4,1/4 NWNW **Sec** 36 **Tw** 8S **Rng** 15E 615 FNL 468 FWL
GPS Coord (UTM) 569283 4436738 **Surface Owner**

Participants

Floyd Bartlett (DOGM), Tim Eaton and Brian Foote (Newfield Production Company), Ben Williams and Pat Rainbolt (Utah Division of Wildlife Resources).

Regional/Local Setting & Topography

The general location is approximately 12 road miles southwest of Myton, UT in the upper portion of the Pleasant Valley Drainage. Wells Draw is approximately 2 miles to the east and the Ute Tribal Indian Reservation 1 mile to the west. Broad flats with rolling hills characterize the area. Flats are often intersected by drainages with gentle to moderate side slopes. Flats at lower elevations to the northeast are frequently used for agriculture. No seeps, springs or streams are known to exist in the immediate area. An occasional pond for livestock watering occurs. Pleasant Valley Wash drains into the Pariette Draw drainage of Duchesne County. The lower reaches of both of these draws contain perennial streams somewhat consisting of irrigation runoff and seepage. Pariette Draw runs into the Green River approximately 6 miles downstream from Ouray, Utah and about 18 miles down drainage from the area. Access is by State and County and existing or proposed oilfield development roads to within 1280 feet of the site. From this point additional construction will be required.

The proposed State 4-36-8-15 oil well location is laid out in a southeasterly to northwesterly direction on a moderately gentle slope leading away from a ridge or rise to the west. The area slopes toward Pleasant Valley Wash. A small drainage meanders across the south part of the location. The pit topsoil will divert it. Following pit closure a diversion needs to be constructed in a location determined most suitable by the operator. A culvert may be needed under the access road for this diversion. The proposed site appears to be a suitable location for constructing a pad and drilling and operating a well. It has been located in the west edge of the drilling window to better fit the terrain.

Both the surface and minerals are owned by SITLA. Ed Bonner and Jim Davis of SITLA were invited to the pre-site evaluation. Neither attended.

Surface Use Plan

Current Surface Use

Grazing
Recreational
Wildlife Habitat

New Road

Miles	Well Pad		Src Const Material	Surface Formation
0.24	Width 199	Length 300	Onsite	UNTA

Ancillary Facilities N

Waste Management Plan Adequate?

Environmental Parameters

Affected Floodplains and/or Wetland N

Flora / Fauna

A desert shrub type consisting of blue gramma grass, halogeton, shadscale, greasewood, black sage, broom snakeweed, needle and thread grass, rabbitbrush, prickly pear, fridge sage, winter fat, curly mesquite grass and spring annuals occupies the area.

Cattle, prairie dogs, antelope, small mammals and birds.

Soil Type and Characteristics

Sandy loam with some surface bedrock

Erosion Issues N**Sedimentation Issues** Y

A small drainage meanders across the south part of the location. The pit topsoil will divert it

Site Stability Issues N**Drainage Diversion Required** Y**Berm Required?** N**Erosion Sedimentation Control Required?**

Following pit closure a diversion needs to be constructed in a location determined most suitable by the operator.

Paleo Survey Run? N **Paleo Potential Observed?** N **Cultural Survey Run?** Y **Cultural Resources?** N

Reserve Pit**Site-Specific Factors****Site Ranking**

Distance to Groundwater (feet) 100 to 200

5

Distance to Surface Water (feet) >1000

0

Dist. Nearest Municipal Well (ft) >5280

0

Distance to Other Wells (feet) >1320

0

Native Soil Type Mod permeability

10

Fluid Type Fresh Water

5

Drill Cuttings Normal Rock

0

Annual Precipitation (inches) <10

0

Affected Populations <10

0

Presence Nearby Utility Conduits Not Present

0

Final Score 20 1 **Sensitivity Level**

Characteristics / Requirements

A 50' x 70' x 8' deep reserve pit is planned in an area of cut on the southwest side of the location. A pit liner is required. Newfield commonly uses a 16-mil liner.

Closed Loop Mud Required? N **Liner Required?** Y **Liner Thickness** 16 **Pit Underlayment Required?** Y


Other Observations / Comments

Floyd Bartlett
Evaluator

3/4/2009
Date / Time

43013342310000 State 4-36-8-15

Casing Schematic



Well name:

43013342310000 State 4-36-8-15

Operator:

Newfield Production Company

String type:

Surface

Project ID:

43-013-34231-0000

Location:

Duchesne County**Design parameters:****Collapse**

Mud weight: 8.400 ppg

Design is based on evacuated pipe.

Minimum design factors:**Collapse:**

Design factor 1.125

Environment:

H2S considered? No

Surface temperature: 65 °F

Bottom hole temperature: 71 °F

Temperature gradient: 1.40 °F/100ft

Minimum section length: 185 ft

Burst:

Design factor 1.00

Cement top: 153 ft

Burst

Max anticipated surface

pressure: 440 psi

Internal gradient: 0.120 psi/ft

Calculated BHP 488 psi

No backup mud specified.

Tension:

8 Round STC: 1.80 (J)

8 Round LTC: 1.80 (J)

Buttress: 1.60 (J)

Premium: 1.50 (J)

Body yield: 1.50 (B)

Tension is based on air weight.

Neutral point: 350 ft

Non-directional string.**Re subsequent strings:**

Next setting depth: 6,280 ft

Next mud weight: 8.400 ppg

Next setting BHP: 2,740 psi

Fracture mud wt: 19.250 ppg

Fracture depth: 500 ft

Injection pressure: 500 psi

Run Seq	Segment Length (ft)	Size (in)	Nominal Weight (lbs/ft)	Grade	End Finish	True Vert Depth (ft)	Measured Depth (ft)	Drift Diameter (in)	Internal Capacity (ft³)
1	400	8.625	24.00	J-55	ST&C	400	400	7.972	143
Run Seq	Collapse Load (psi)	Collapse Strength (psi)	Collapse Design Factor	Burst Load (psi)	Burst Strength (psi)	Burst Design Factor	Tension Load (Kips)	Tension Strength (Kips)	Tension Design Factor
1	175	1370	7.849	488	2950	6.05	10	244	25.42 J

Prepared Helen Sadik-Macdonald
by: Div of Oil, Gas & Mining

Phone: 810-538-5357

Date: April 15, 2009
Salt Lake City, Utah**ENGINEERING STIPULATIONS: NONE**

Collapse strength is based on the Westcott, Dunlop & Kemler method of biaxial correction for tension.

Collapse is based on a vertical depth of 400 ft, a mud weight of 8.4 ppg. The casing is considered to be evacuated for collapse purposes.

Burst strength is not adjusted for tension.

Engineering responsibility for use of this design will be that of the purchaser.

Well name:	43013342310000 State 4-36-8-15	
Operator:	Newfield Production Company	Project ID:
String type:	Production	43-013-34231-0000
Location:	Duchesne County	

Design parameters:

Collapse

Mud weight: 8.400 ppg
Design is based on evacuated pipe.

Minimum design factors:

Collapse:

Design factor 1.125

Burst:

Design factor 1.00

Environment:

H2S considered? No
Surface temperature: 65 °F
Bottom hole temperature: 153 °F
Temperature gradient: 1.40 °F/100ft
Minimum section length: 368 ft
Cement top: 671 ft

Burst

Max anticipated surface pressure: 1,359 psi
Internal gradient: 0.220 psi/ft
Calculated BHP 2,740 psi

No backup mud specified.

Tension:

8 Round STC: 1.80 (J)
8 Round LTC: 1.80 (J)
Buttress: 1.60 (J)
Premium: 1.50 (J)
Body yield: 1.50 (B)

Non-directional string.

Tension is based on buoyed weight.
Neutral point: 5,482 ft

Run Seq	Segment Length (ft)	Size (in)	Nominal Weight (lbs/ft)	Grade	End Finish	True Vert Depth (ft)	Measured Depth (ft)	Drift Diameter (in)	Internal Capacity (ft³)
1	6280	5.5	15.50	J-55	LT&C	6280	6280	4.825	839.3
Run Seq	Collapse Load (psi)	Collapse Strength (psi)	Collapse Design Factor	Burst Load (psi)	Burst Strength (psi)	Burst Design Factor	Tension Load (Kips)	Tension Strength (Kips)	Tension Design Factor
1	2740	4040	1.474	2740	4810	1.76	85	217	2.55 J

Prepared by: Helen Sadik-Macdonald
Div of Oil, Gas & Mining

Phone: 810-538-5357

Date: April 15, 2009
Salt Lake City, Utah

ENGINEERING STIPULATIONS: NONE

Collapse strength is based on the Westcott, Dunlop & Kemler method of biaxial correction for tension.

Collapse is based on a vertical depth of 6280 ft, a mud weight of 8.4 ppg. The casing is considered to be evacuated for collapse purposes.

Burst strength is not adjusted for tension.

Engineering responsibility for use of this design will be that of the purchaser.

BOPE REVIEW

Newfield State 4-36-8-15

API 43-013-34231-0000

INPUT

Well Name

Casing Size (")

Setting Depth (TVD)

Previous Shoe Setting Depth (TVD)

Max Mud Weight (ppg)

BOPE Proposed (psi)

Casing Internal Yield (psi)

Operators Max Anticipated Pressure (psi)

Newfield State 4-36-8-15 API 43-013-34231-0000			
String 1	String 2		
8 5/8	5 1/2		
400	6280		
0	400		
8.4	8.4	✓	
0	2000		
2950	4810		
2719	8.3 ppg	✓	

Calculations	String 1	8 5/8 "	
Max BHP [psi]	.052*Setting Depth*MW =	175	
			BOPE Adequate For Drilling And Setting Casing at Depth?
MASP (Gas) [psi]	Max BHP-(0.12*Setting Depth) =	127	NO Air drill
MASP (Gas/Mud) [psi]	Max BHP-(0.22*Setting Depth) =	87	NO
			*Can Full Expected Pressure Be Held At Previous Shoe?
Pressure At Previous Shoe	Max BHP-.22*(Setting Depth - Previous Shoe Depth) =	87	NO Reasonable Depth in Grey
Required Casing/BOPE Test Pressure		400 psi	
*Max Pressure Allowed @ Previous Casing Shoe =		0 psi	*Assumes 1psi/ft frac gradient

Calculations	String 2	5 1/2 "	
Max BHP [psi]	.052*Setting Depth*MW =	2743	
			BOPE Adequate For Drilling And Setting Casing at Depth?
MASP (Gas) [psi]	Max BHP-(0.12*Setting Depth) =	1990	YES Air Drill
MASP (Gas/Mud) [psi]	Max BHP-(0.22*Setting Depth) =	1362	YES ✓
			*Can Full Expected Pressure Be Held At Previous Shoe?
Pressure At Previous Shoe	Max BHP-.22*(Setting Depth - Previous Shoe Depth) =	1450	← NO Reasonable
Required Casing/BOPE Test Pressure		2000 psi	
*Max Pressure Allowed @ Previous Casing Shoe =		400 psi ✓	*Assumes 1psi/ft frac gradient

From: Jim Davis
To: Bonner, Ed; Mason, Diana
Date: 4/2/2009 10:49 AM
Subject: Newfield Approvals (14)

CC: Garrison, LaVonne; mcrozier@newfield.com; teaton@newfield.com

The following wells have been approved by SITLA including arch and paleo clearance.

Newfield Production's State 5-36-8-15 [API #4301334230]

Newfield Production's State 2-36-8-15 [API #4301334233]

Newfield Production's State 15-36-8-15 [API #4301334221]

Newfield Production's State 14-36-8-15 [API #4301334222]

Newfield Production's State 13-36-8-15 [API #4301334223]

Newfield Production's State 12-36-8-15 [API #4301334224]

Newfield Production's State 11-36-8-15 [API #4301334225]

Newfield Production's State 1-36-8-15 [API #4301334234]

Newfield Production's State 10-36-8-15 [API #4301334226]

Newfield Production's State 9-36-8-15 [API #4301334227]

Newfield Production's State 8-36-8-15 [API #4301334228]

Newfield Production's State 6-36-8-15 [API #4301334229]

Newfield Production's State 3-36-8-15 [API #4301334232]

Newfield Production's State 4-36-8-15 [API #4301334231]

-Jim

Jim Davis
Utah Trust Lands Administration
jimdavis1@utah.gov
Phone: (801) 538-5156

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

FORM 3

AMENDED REPORT ☐
(highlight changes)

APPLICATION FOR PERMIT TO DRILL				5. MINERAL LEASE NO: ML-21835	6. SURFACE: State
1A. TYPE OF WORK: DRILL <input checked="" type="checkbox"/> REENTER <input type="checkbox"/> DEEPEN <input type="checkbox"/>				7. IF INDIAN, ALLOTTEE OR TRIBE NAME: NA	
8. TYPE OF WELL: OIL <input checked="" type="checkbox"/> GAS <input type="checkbox"/> OTHER _____ SINGLE ZONE <input checked="" type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/>				8. UNIT or CA AGREEMENT NAME: NA	
2. NAME OF OPERATOR: Newfield Production Company				9. WELL NAME and NUMBER: State 4-36-8-15	
3. ADDRESS OF OPERATOR: Route #3 Box 3630 CITY Myton STATE UT ZIP 84052				10. FIELD AND POOL, OR WMLCAT: Monument Butte	
4. LOCATION OF WELL (FOOTAGES) AT SURFACE: NW/NW 615' FNL 468' FWL AT PROPOSED PRODUCING ZONE: 4436748 Y -110.187587				11. QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: NWNW 36 8S 15E	
14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE: Approximately 12.5 miles southwest of Myton, Utah				12. COUNTY: Duchesne	13. STATE: UTAH
15. DISTANCE TO NEAREST PROPERTY OR LEASE LINE (FEET) Approx. 468' f/lse line, NA' f/unit line		16. NUMBER OF ACRES IN LEASE: 640.00 acres		17. NUMBER OF ACRES ASSIGNED TO THIS WELL: 40 acres	
18. DISTANCE TO NEAREST WELL (DRILLING, COMPLETED, OR APPLIED FOR) ON THIS LEASE (FEET) Approx. 1791'		19. PROPOSED DEPTH: 6,280		20. BOND DESCRIPTION: #B001834	
21. ELEVATIONS (SHOW WHETHER DF, RT, GR, ETC.): 5718' GL		22. APPROXIMATE DATE WORK WILL START: 3rd Qtr. 2009		23. ESTIMATED DURATION: (7) days from SPUD to rig release	

24. PROPOSED CASING AND CEMENTING PROGRAM							
SIZE OF HOLE	CASING SIZE, GRADE, AND WEIGHT PER FOOT			SETTING DEPTH	CEMENT TYPE, QUANTITY, YIELD, AND SLURRY WEIGHT		
12 1/4	8 5/8	J-55	24.0	400	Class G w/2% CaCl	155 sx +/-	1.17 15.8
7 7/8	5 1/2	J-55	15.5	6,280	Lead(Prem Lite II)	275 sx +/-	3.26 11.0
					Tail (50/50 Poz)	450 sx +/-	1.24 14.3

25. ATTACHMENTS

VERIFY THE FOLLOWING ARE ATTACHED IN ACCORDANCE WITH THE UTAH OIL AND GAS CONSERVATION GENERAL RULES:

<input checked="" type="checkbox"/> WELL PLAT OR MAP PREPARED BY LICENSED SURVEYOR OR ENGINEER	<input checked="" type="checkbox"/> COMPLETE DRILLING PLAN
<input checked="" type="checkbox"/> EVIDENCE OF DIVISION OF WATER RIGHTS APPROVAL FOR USE OF WATER	<input type="checkbox"/> FORM 5, IF OPERATOR IS PERSON OR COMPANY OTHER THAN THE LEASE OWNER

NAME (PLEASE PRINT) Mandie Crozier TITLE Regulatory Specialist

SIGNATURE *Mandie Crozier* DATE 4/2/09

(This space for State use only)

API NUMBER ASSIGNED: 43-013-34231

Approved by the
Utah Division of
Oil, Gas and Mining
APPROVAL:

RECEIVED


APR 02 2009

DIV. OF OIL, GAS & MINING

Date: 04-27-09
(See Instructions on Reverse Side)
By: *[Signature]*

NEWFIELD PRODUCTION COMPANY

A horizontal bar scale with alternating black and white segments. Above the bar, the markings 1000', 500', 0', 500', and 1000' are printed from left to right. Below the bar, the words 'BAR' and 'SCALE' are printed, centered under the first half and second half of the bar respectively.



THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS
PREPARED FROM FIELD NOTES OF ACTUAL SURVEYS
MADE BY ME OR UNDER MY SUPERVISION AND THAT
THE SAME ARE TRUE AND CORRECT TO THE BEST OF
MY KNOWLEDGE AND BELIEF. No. 189377

STACY W. STEWART
REGISTERED LAND SURVEYOR
REGISTRATION No. 10037
STATE OF UTAH

TRI STATE LAND SURVEYING & CONSULTING

180 NORTH VERNAL AVE. - VERNAL, UTAH 84078
(435) 781-2501

DATE SURVEYED:
12-01-08


SURVEYED BY: T.H.

DATE DRAWN:
12-20-08

DRAWN BY: F.T.M.

REVISÉ:

SCALE: 1" = 1000'



 = SECTION CORNERS LOCATED

BASIS OF ELEV;
U.S.G.S. 7-1/2 min QUAD (MYTON SW)

STATE 4-36-8-15
(Surface Location) NAD 83
LATITUDE = 40° 04' 48.12"
LONGITUDE = 110° 11' 17.67"

NEWFIELD PRODUCTION COMPANY
STATE 4-36-8-15
NW/NW SECTION 36, T8S, R15E
DUCHESNE COUNTY, UTAH

TEN POINT DRILLING PROGRAM

1. GEOLOGIC SURFACE FORMATION:

Uinta formation of Upper Eocene Age

2. ESTIMATED TOPS OF IMPORTANT GEOLOGIC MARKERS:

Uinta	0 – 1,530'
Green River	1,530'
Wasatch	6,280'

3. ESTIMATED DEPTHS OF ANTICIPATED WATER, OIL, GAS OR MINERALS:

Green River Formation (Oil) 1,530' – 6,280'

Fresh water may be encountered in the Uinta Formation, but would not be expected below about 350'. All water shows and water bearing geologic units shall be reported to the geologic and engineering staff of the Vernal Office prior to running the next string of casing or before plugging orders are requested. All water shows must be reported within one (1) business day after being encountered.

All usable (<10,000 PPM TDS) water and prospectively valuable minerals (as described by BLM at onsite) encountered during drilling will be recorded by depth and adequately protected. This information shall be reported to the Vernal Office.

Detected water flows shall be sampled, analyzed, and reported to the geologic & engineering staff of the Vernal Office. The office may request additional water samples for further analysis. Usage of the State of Utah form *Report of Water Encountered* is acceptable, but not required.

The following information is requested for water shows and samples where applicable:

Location & Sampled Interval	Date Sampled
Flow Rate	Temperature
Hardness	pH
Water Classification (State of Utah)	Dissolved Calcium (Ca) (mg/l)
Dissolved Iron (Fe) (ug/l)	Dissolved Sodium (Na) (mg/l)
Dissolved Magnesium (Mg) (mg/l)	Dissolved Carbonate (CO ₃) (mg/l)
Dissolved Bicarbonate (NaHCO ₃) (mg/l)	Dissolved Chloride (Cl) (mg/l)
Dissolved Sulfate (SO ₄) (mg/l)	Dissolved Total Solids (TDS) (mg/l)

4. PROPOSED CASING PROGRAM:

Surface Casing: 8-5/8" J-55 24# w/ST&C collars; set at 400' (New)
Production Casing: 5-1/2" J-55, 15.5# w/LT&C collars; set at TD (New or used, inspected).

5. MINIMUM SPECIFICATIONS FOR PRESSURE CONTROL:

The operator's minimum specifications for pressure control equipment are as follows:

RECEIVED

APR 02 2009

DIV. OF OIL, GAS & MINING

An 8" Double Ram Hydraulic unit with a closing unit will be utilized. Function test of BOP's will be check daily.

Refer to **Exhibit C** for a diagram of BOP equipment that will be used on this well.

6. **TYPE AND CHARACTERISTICS OF THE PROPOSED CIRCULATION MUDS:**

From surface to ± 350 feet will be drilled with an air/mist system. The air rig is equipped with a 6 1/2" blooie line that is straight run and securely anchored. The blooie line is used with a discharge less than 100 ft from the wellbore in order to minimize the well pad size. The blooie line is not equipped with an automatic igniter or continuous pilot light and the compressor is located less than 100 ft from the well bore due to the low possibility of combustion with the air dust mixture. The trailer mounted compressor (capacity of 2000 CFM) has a safety shut-off valve which is located 15 feet from the air rig. A truck with 70 bbls of water is on stand by to be used as kill fluid, if necessary. From about ± 350 feet to TD, a fresh water system will be utilized. Clay inhibition and hole stability will be achieved with a KCl substitute additive. This additive will be identified in the APD and reviewed to determine if the reserve pit shall be lined. This fresh water system will typically contain Total Dissolved Solids (TDS) of less than 3000 PPM. Anticipated mud weight is 8.4 lbs/gal. If necessary to control formation fluids or pressure, the system will be weighted with the addition of bentonite gel, and if pressure conditions warrant, with barite.

No chromate additives will be used in the mud system on Federal and/or Indian lands without prior BLM approval to ensure adequate protection of fresh aquifers.

No chemicals subject to reporting under SARA Title III in an amount equal to or greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completing of this well. Furthermore, no extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities, will be used, produced, stored, transported, or disposed of in association with the drilling, testing, or completing of this well.

Hazardous substances specifically listed by the EPA as a hazardous waste or demonstrating a characteristic of a hazardous waste will not be used in drilling, testing, or completion operations.

Newfield Production will **visually** monitor pit levels and flow from the well during drilling operations.

7. **AUXILIARY SAFETY EQUIPMENT TO BE USED:**

Auxiliary safety equipment will be a Kelly Cock, bit float, and a TIW valve with drill pipe threads.

8. **TESTING, LOGGING AND CORING PROGRAMS:**

The logging program will consist of a Dual Induction, Gamma Ray and Caliper log from TD to base of surface casing @ 300' +/-, and a Compensated Neutron-Formation Density Log from TD to 3500' +/- . A cement bond log will be run from PBTD to cement top. No drill stem testing or coring is planned for this well.

9. **ANTICIPATED ABNORMAL PRESSURE OR TEMPERATURE:**

No abnormal temperatures or pressures are anticipated. No hydrogen sulfide has been encountered or is known to exist from previous drilling in the area at this depth. Maximum anticipated bottomhole pressure will approximately equal total depth in feet multiplied by a 0.433 psi/foot gradient.

10. **ANTICIPATED STARTING DATE AND DURATION OF THE OPERATIONS:**

It is anticipated that the drilling operations will commence the third quarter of 2009, and take approximately seven (7) days from spud to rig release.

NEWFIELD PRODUCTION COMPANY
STATE 4-36-8-15
NW/NW SECTION 36, T8S, R15E
DUCHESNE COUNTY, UTAH

THIRTEEN POINT SURFACE PROGRAM

1. **EXISTING ROADS**

See attached **Topographic Map "A"**

To reach Newfield Production Company well location site State 4-36-8-15 located in the NW¼ NW¼ Section 36, T8S, R15E, S.L.B. & M., Duchesne County, Utah:

Proceed southwesterly out of Myton, Utah along Highway 40 - 1.4 miles \pm to the junction of this highway and UT State Hwy 53; proceed southwesterly - 6.4 miles to it's junction with an existing road to the southwest; proceed southwesterly - 2.8 miles \pm to it's junction with an existing road to the south; proceed southeasterly - 0.6 miles \pm to it's junction with an existing road to the southwest; proceed in a southwesterly direction - 0.9 miles \pm to it's junction with the beginning of the proposed access road to the east; proceed easterly along the proposed access road - 2,250' \pm to the proposed well location.

The highways mentioned in the foregoing paragraph are bituminous surfaced roads to the point where Highway 216 exists to the South, thereafter the roads are constructed with existing materials and gravel. The highways are maintained by Utah State road crews. All other roads are maintained by County crews.

The aforementioned dirt oil field service roads and other roads in the vicinity are constructed out of existing native materials that are prevalent to the existing area they are located in and range from clays to a sandy-clay shale material.

The roads for access during the drilling, completion and production phase will be maintained at the standards required by the State of Utah, or other controlling agencies. This maintenance will consist of some minor grader work for smoothing road surfaces and for snow removal.

2. **PLANNED ACCESS ROAD**

Approximately 2,250' miles of access road is proposed and will require a separate R.O.W. from the Bureau of Land Management See attached **Topographic Map "B"**.

The proposed access road will be an 18' crown road (9' either side of the centerline) with drainage ditches along either side of the proposed road whether it is deemed necessary in order to handle any run-off from normal meteorological conditions that are prevalent to this area. The maximum grade will be less than 8%.

There will be no culverts required along this access road. There will be barrow ditches and turnouts as needed along this road.

There are no fences encountered along this proposed road. There will be no new gates or cattle guards required.

All construction material for this access road will be borrowed material accumulated during construction of the access road.

3. **LOCATION OF EXISTING WELLS**

Refer to **EXHIBIT B**.

4. **LOCATION OF EXISTING AND/OR PROPOSED FACILITIES**

There are no existing facilities that will be used by this well.

It is anticipated that this well will be a producing oil well.

Upon construction of a tank battery, the well pad will be surrounded by a dike of sufficient capacity to contain at minimum 110% of the largest tank volume within the facility battery.

Tank batteries will be built to State specifications.

All permanent (on site for six (6) months or longer) structures, constructed or installed (including pumping units), will be painted a flat, non-reflective, earth tone color to match one of the standard environmental colors, as determined by the Rocky Mountain Five State Interagency Committee. All facilities will be painted within six months of installation.

5. **LOCATION AND TYPE OF WATER SUPPLY**

Newfield Production will transport water by truck for drilling purposes from the following water sources:

Johnson Water District
Water Right: 43-7478

Neil Moon Pond
Water Right: 43-11787

Maurice Harvey Pond
Water Right: 47-1358

Newfield Collector Well
Water Right: 41-3530 (A30414DV, contracted with the Duchesne County Conservancy District).

There will be no water well drilled at this site

6. **SOURCE OF CONSTRUCTION MATERIALS**

All construction material for this location shall be borrowed material accumulated during construction of the location site and access road.

A mineral material application is not required for this location.

7. **METHODS FOR HANDLING WASTE DISPOSAL**

A small reserve pit (90' x 40' x 8' deep, or less) will be constructed from native soil and clay materials. The reserve pit will receive the processed drill cutting (wet sand, shale & rock) removed from the wellbore. Any drilling fluids, which do accumulate in the pit as a result of shale-shaker carryover, cleaning of the sand trap, etc., will be promptly reclaimed. All drilling

fluids will be fresh water based, typically containing Total Dissolved Solids of less than 3000 PPM. No potassium chloride, chromates, trash, debris, nor any other substance deemed hazardous will be placed in this pit. A 16 mil liner with felt will be required. Newfield requests approval that a flare pit be constructed and utilized on this location.

A portable toilet will be provided for human waste.

A trash basket will be provided for garbage (trash) and hauled away to an approved disposal site at the completion of the drilling activities.

Immediately upon first production, all produced water will be confined to a steel storage tank. If the production water meets quality guidelines, it is transported to the Ashley, Monument Butte, Jonah, and Beluga water injection facilities by company or contract trucks. Subsequently, the produced water is injected into approved Class II wells to enhance Newfield's secondary recovery project.

Water not meeting quality criteria, is disposed at Newfield's Pariette #4 disposal well (Sec. 7, T9S R19E) or at State of Utah approved surface disposal facilities.

8. **ANCILLARY FACILITIES:**

There are no ancillary facilities planned for at the present time and none foreseen in the near future.

9. **WELL SITE LAYOUT:**

See attached Location Layout Sheet.

Fencing Requirements

All pits will be fenced according to the following minimum standards:

- a) A 39-inch net wire shall be used with at least one strand of barbed wire on top of the net.
- b) The net wire shall be no more than two (2) inches above the ground. The barbed wire shall be three (3) inches above the net wire. Total height of the fence shall be at least forty-two (42) inches.
- c) Corner posts shall be centered and/or braced in such a manner to keep tight at all times
- d) Standard steel, wood or pipe posts shall be used between the corner braces. Maximum distance between any two posts shall be no greater than sixteen (16) feet.
- e) All wire shall be stretched, by using a stretching device, before it is attached to the corner posts.

The reserve pit fencing will be on three (3) sides during drilling operations and on the fourth side when the rig moves off location. Pits will be fenced and maintained until cleanup.

10. **PLANS FOR RESTORATION OF SURFACE:**

- a) **Producing Location**

Immediately upon well completion, the location and surrounding area will be cleared of all unused tubing, equipment, debris, material, trash and junk not required for production.

The reserve pit and that portion of the location not needed for production facilities/operations will be recontoured to the approximated natural contours. Weather permitting, the reserve pit will be reclaimed within one hundred twenty (120) days from the date of well completion. Before any dirt work takes place, the reserve pit must have all fluids and hydrocarbons removed.

b) **Dry Hole Abandoned Location**

At such time as the well is plugged and abandoned, the operator shall submit a subsequent report of abandonment and the State of Utah will attach the appropriate surface rehabilitation conditions of approval.

11. **SURFACE OWNERSHIP:** State of Utah.

12. **OTHER ADDITIONAL INFORMATION:**

Newfield Production Company requests 2,250' of disturbed area be granted to allow for construction of the proposed surface gas lines. It is proposed that the disturbed area will temporarily be 50' wide to allow for construction of a 10" or smaller gas gathering line, and a 3" poly fuel gas line, with a permanent width of 30' upon completion of the proposed gas lines. The construction phase of the proposed gas lines will last approximately (5) days. Both lines will tie in to the existing pipeline infrastructure. **Refer to Topographic Map "C."**

Newfield Production Company requests 2,250' of disturbed area be granted to allow for construction of the proposed water lines. It is proposed that the disturbed area will temporarily be 50' wide to allow for construction of a buried 3" steel water injection line and a buried 3" poly water return line, with a permanent width of 30' upon completion of the proposed water return line. The construction phase of the proposed water lines will last approximately (5) days. **Refer to Topographic Map "C."** In the event that the proposed well is converted to a water injection well, a separate injection permit will be applied for through the proper agencies.

The Archaeological Survey is attached. MOAC Report #08-301, 1/26/09. See attached report cover page, Exhibit "D". The Paleontological Resource Survey will be forthcoming.

- a) Newfield Production Company is responsible for informing all persons in the area who are associated with this project that they will be subject to prosecution for knowingly disturbing historic or archaeological sites, or for collecting artifacts. If historic or archaeological materials are uncovered during construction, Newfield is to immediately stop work that might further disturb such materials and contact the Authorized Officer.
- b) Newfield Production will control noxious weeds along rights-of-way for roads, pipelines, well sites or other applicable facilities. On State administered land it is required that a Pesticide Use Proposal shall be submitted and given approval prior to the application of herbicides or other possible hazardous chemicals.
- c) Drilling rigs and/or equipment used during drilling operations on this well site will not be stacked or stored on State Lands after the conclusion of drilling operations or at any other time without State authorization. However, if State authorization is obtained, it is only a temporary measure to allow time to make arrangements for permanent storage on commercial facilities.

Additional Surface Stipulations

All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws and regulations, Onshore Oil and Gas Orders, the approved plan of operations and any applicable Notice to Lessees. A copy of these conditions will be furnished to the field representative to ensure compliance.

Hazardous Material Declaration

Newfield Production Company guarantees that during the drilling and completion of the State 4-36-8-15, Newfield will not use, produce, store, transport or dispose 10,000# annually of any of the hazardous chemicals contained in the Environmental Protection Agency's consolidated list of chemicals subject to reporting under Title III Superfund Amendments and Reauthorization Act (SARA) of 1986. Newfield also guarantees that during the drilling and completion of the State 4-36-8-15 Newfield will use, produce, store, transport or dispose less than the threshold planning quantity (T.P.Q.) of any extremely hazardous substances as defined in 40 CFR 355.

A complete copy of the approved APD, if applicable, shall be on location during the construction of the location and drilling activities.

Newfield Production Company or a contractor employed by Newfield Production shall contact the State office at (801) 722-3417, 48 hours prior to construction activities.

The State office shall be notified upon site completion prior to moving on the drilling rig.

13. **LESSEE'S OR OPERATOR'S REPRESENTATIVE AND CERTIFICATION:**

Representative


Name: Dave Allred
Address: Newfield Production Company
Route 3, Box 3630
Myton, UT 84052
Telephone: (435) 646-3721

Certification

Please be advised that Newfield Production Company is considered to be the operator of well #4-36-8-15, NW/NW Section 36, T8S, R15E, Duchesne County, Utah and is responsible under the terms and conditions of the lease for the operations conducted upon the leased lands. Bond coverage is provided by Bond #B001834.

I hereby certify that the proposed drill site and access route have been inspected, and I am familiar with the conditions which currently exist; that the statements made in this plan are true and correct to the best of my knowledge; and that the work associated with the operations proposed here will be performed by Newfield Production Company and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of the 18 U.S.C. 1001 for the filing of a false statement.


2/27/09
Date


Mandie Crozier
Regulatory Specialist
Newfield Production Company

NEWFIELD PRODUCTION COMPANY

STATE 4-36-8-15

Section 36, T8S, R15E, S.L.B.&M.



Note:
Flare pit is to be located a minimum of 80' from well head.

REFERENCE POINTS




220' NORTHEAST = 5713.6'
270' NORTHEAST = 5710.2'
170' SOUTHEAST = 5708.5'
220' SOUTHEAST = 5708.2'

SURVEYED BY: T.H.	DATE SURVEYED: 12-01-08
DRAWN BY: F.T.M.	DATE DRAWN: 12-20-08
SCALE: 1" = 50'	REVISED:

Tri State
Land Surveying, Inc.
(435) 781-2501
180 NORTH VERNAL AVE. VERNAL, UTAH 84078

NEWFIELD PRODUCTION COMPANY

CROSS SECTIONS STATE 4-36-8-15



NOTE:
UNLESS OTHERWISE
NOTED ALL CUT/FILL
SLOPES ARE AT 1.5:1


ESTIMATED EARTHWORK QUANTITIES (No Shrink or swell adjustments have been used) (Expressed in Cubic Yards)				
ITEM	CUT	FILL	6" TOPSOIL	EXCESS
PAD	2,420	2,410	Topsoil is not included in Pad Cut	10
PIT	640	0		640
TOTALS	3,060	2,410	1,060	650

SURVEYED BY: T.H.	DATE SURVEYED: 12-01-08
DRAWN BY: F.T.M.	DATE DRAWN: 12-20-08
SCALE: 1" = 50'	REVISED:

Tri State
Land Surveying, Inc.
180 NORTH VERNAL AVE. VERNAL, UTAH 84078
(435) 781-2501

NEWFIELD PRODUCTION COMPANY

TYPICAL RIG LAYOUT STATE 4-36-8-15



SURVEYED BY: T.H.	DATE SURVEYED: 12-01-08
DRAWN BY: F.T.M.	DATE DRAWN: 12-20-08
SCALE: 1" = 50'	REVISED:


Tri State
 Land Surveying, Inc.
 180 NORTH VERNAL AVE. VERNAL, UTAH 84078
 (435) 781-2501


Legend

- Existing Road
- Proposed Access

TOPOGRAPHIC MAP

"A"





NEWFIELD
Exploration Company

State 4-36-8-15
SEC. 36, T8S, R15E, S.L.B.&M.





Tri-State
Land Surveying Inc.
(435) 781-2501
180 North Vernal Ave. Vernal, Utah 84078

SCALE: 1" = 2,000'

DRAWN BY: mw

DATE: 12-29-2008


Legend




Existing Road


Proposed Access

TOPOGRAPHIC MAP

"B"



 <p>NEWFIELD Exploration Company</p>		 <p>Tri-State Land Surveying Inc. (435) 781-2501 180 North Vernal Ave. Vernal, Utah 84078</p>	<p>Legend</p> <ul style="list-style-type: none"> — Roads - - - Proposed Gas Line - - - Proposed Water Line
<p>State 4-36-8-15 SEC. 36, T8S, R15E, S.L.B.&M.</p>		<p>SCALE: 1" = 2,000' DRAWN BY: mw DATE: 12-29-2008</p>	<p>TOPOGRAPHIC MAP</p> <p>"C"</p>



2-M SYSTEM

Blowout Prevention Equipment Systems




EXHIBIT C

Exhibit "D"

CULTURAL RESOURCE INVENTORY OF
NEWFIELD EXPLORATION'S FOUR BLOCK PARCELS
(T8S, R15E, SECTIONS 25, 26, 35, AND 36)
DUCHESNE COUNTY, UTAH

By:

Nicole Shelnut

Prepared For:

Bureau of Land Management
Vernal Field Office
and
School & Institutional
Trust Lands Administration

Prepared Under Contract With:

Newfield Exploration Company
Rt. 3 Box 3630
Myton, UT 84052

Prepared By:

Montgomery Archaeological Consultants, Inc.
P.O. Box 219
Moab, Utah 84532

MOAC Report No. 08-301

January 26, 2009

United States Department of Interior (FLPMA)
Permit No. 08-UT-60122

State of Utah Antiquities Project (Survey)
Permit No. U-08-MQ-1227b,s



JON M. HUNTSMAN, JR.
Governor

GARY R. HERBERT
Lieutenant Governor

State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER
Executive Director

Division of Oil, Gas and Mining

JOHN R. BAZA
Division Director

April 27, 2009

Newfield Production Company
Rt. #3, Box 3630
Myton, UT 84052

Re: State 4-36-8-15 Well, 615' FNL, 468' FWL, NW NW, Sec. 36, T. 8 South, R. 15 East,
Duchesne County, Utah

Gentlemen:

Pursuant to the provisions and requirements of Utah Code Ann. § 40-6-1 *et seq.*, Utah Administrative Code R649-3-1 *et seq.*, and the attached Conditions of Approval, approval to drill the referenced well is granted.

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date. The API identification number assigned to this well is 43-013-34231.

Sincerely,

Gil Hunt
Associate Director

pab
Enclosures

cc: Duchesne County Assessor
SITLA



Operator: Newfield Production Company

Well Name & Number State 4-36-8-15

API Number: 43-013-34231

Lease: ML-21835

Location: NW NW Sec. 36 T. 8 South R. 15 East

Conditions of Approval

1. General

Compliance with the requirements of Utah Admin. R. 649-1 *et seq.*, the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

2. Notification Requirements

The operator is required to notify the Division of Oil, Gas and Mining of the following action during drilling of this well:

- 24 hours prior to cementing or testing casing – contact Dan Jarvis
- 24 hours prior to testing blowout prevention equipment – contact Dan Jarvis
- 24 hours prior to spudding the well – contact Carol Daniels
- Within 24 hours of any emergency changes made to the approved drilling program – contact Dustin Doucet
- Prior to commencing operations to plug and abandon the well – contact Dan Jarvis

The operator is required to get approval from the Division of Oil, Gas and Mining before performing any of the following actions during the drilling of this well:

- Plugging and abandonment or significant plug back of this well – contact Dustin Doucet
- Any changes to the approved drilling plan – contact Dustin Doucet

The following are Division of Oil, Gas and Mining contacts and their telephone numbers (please leave a voice mail message if the person is not available to take the call):

- Dan Jarvis at: (801) 538-5338 office (801) 942-0871 home
- Carol Daniels at: (801) 538-5284 office
- Dustin Doucet at: (801) 538-5281 office (801) 733-0983 home

3. Reporting Requirements

All required reports, forms and submittals will be promptly filed with the Division, including but not limited to the Entity Action Form (Form 6), Report of Water Encountered During Drilling (Form 7), Weekly Progress Reports for drilling and completion operations, and Sundry Notices and Reports on Wells requesting approval of change of plans or other operational actions.

4. Compliance with the State of Utah Antiquities Act forbids disturbance of archeological, historical, or paleontological remains. Should archeological, historical or paleontological remains be encountered during your operations, you are required to immediately suspend all operations and immediately inform the Trust Lands Administration and the Division of State History of the discovery of such remains.
5. Compliance with the Conditions of Approval/Application for Permit to Drill outlined in the Statement of Basis. (Copy Attached)
6. This proposed well is located in an area for which drilling units (well spacing patterns) have not been established through an order of the Board of Oil, Gas and Mining (the "Board"). In order to avoid the possibility of waste or injury to correlative rights, the operator is requested, once the well has been drilled, completed, and has produced, to analyze geological and engineering data generated therefrom, as well as any similar data from surrounding areas if available. As soon as is practicable after completion of its analysis, and if the analysis suggests an area larger than the quarter-quarter section upon which the well is located is being drained, the operator is requested to seek an appropriate order from the Board establishing drilling and spacing units in conformance with such analysis by filing a Request for Agency Action with the Board.
7. Surface casing shall be cemented to the surface.

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING		FORM 9			
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.		5. LEASE DESIGNATION AND SERIAL NUMBER: ML-21835			
1. TYPE OF WELL Oil Well		6. IF INDIAN, ALLOTTEE OR TRIBE NAME:			
2. NAME OF OPERATOR: NEWFIELD PRODUCTION COMPANY		7. UNIT or CA AGREEMENT NAME: GMBU (GRRV)			
3. ADDRESS OF OPERATOR: Rt 3 Box 3630 , Myton, UT, 84052		8. WELL NAME and NUMBER: STATE 4-36-8-15			
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0615 FNL 0468 FWL QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: NWNW Section: 36 Township: 08.0S Range: 15.0E Meridian: S		9. API NUMBER: 43013342310000			
PHONE NUMBER: 435 646-4825 Ext		9. FIELD and POOL or WILDCAT: MONUMENT BUTTE			
COUNTY: DUCHESNE		STATE: UTAH			
11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA					
TYPE OF SUBMISSION	TYPE OF ACTION				
<input checked="" type="checkbox"/> NOTICE OF INTENT Approximate date work will start: 4/27/2010 <input type="checkbox"/> SUBSEQUENT REPORT Date of Work Completion: <input type="checkbox"/> SPUD REPORT Date of Spud: <input type="checkbox"/> DRILLING REPORT Report Date:	<table style="width: 100%; border: none;"> <tr> <td style="width: 33%; vertical-align: top;"> <input type="checkbox"/> ACIDIZE <input type="checkbox"/> CHANGE TO PREVIOUS PLANS <input type="checkbox"/> CHANGE WELL STATUS <input type="checkbox"/> DEEPEN <input type="checkbox"/> OPERATOR CHANGE <input type="checkbox"/> PRODUCTION START OR RESUME <input type="checkbox"/> REPERFORATE CURRENT FORMATION <input type="checkbox"/> TUBING REPAIR <input type="checkbox"/> WATER SHUTOFF <input type="checkbox"/> WILDCAT WELL DETERMINATION </td> <td style="width: 33%; vertical-align: top;"> <input type="checkbox"/> ALTER CASING <input type="checkbox"/> CHANGE TUBING <input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS <input type="checkbox"/> FRACTURE TREAT <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> RECLAMATION OF WELL SITE <input type="checkbox"/> SIDETRACK TO REPAIR WELL <input type="checkbox"/> VENT OR FLARE <input type="checkbox"/> SI TA STATUS EXTENSION <input type="checkbox"/> OTHER </td> <td style="width: 33%; vertical-align: top;"> <input type="checkbox"/> CASING REPAIR <input type="checkbox"/> CHANGE WELL NAME <input type="checkbox"/> CONVERT WELL TYPE <input type="checkbox"/> NEW CONSTRUCTION <input type="checkbox"/> PLUG BACK <input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION <input type="checkbox"/> TEMPORARY ABANDON <input type="checkbox"/> WATER DISPOSAL <input checked="" type="checkbox"/> APD EXTENSION OTHER: _____ </td> </tr> </table>		<input type="checkbox"/> ACIDIZE <input type="checkbox"/> CHANGE TO PREVIOUS PLANS <input type="checkbox"/> CHANGE WELL STATUS <input type="checkbox"/> DEEPEN <input type="checkbox"/> OPERATOR CHANGE <input type="checkbox"/> PRODUCTION START OR RESUME <input type="checkbox"/> REPERFORATE CURRENT FORMATION <input type="checkbox"/> TUBING REPAIR <input type="checkbox"/> WATER SHUTOFF <input type="checkbox"/> WILDCAT WELL DETERMINATION	<input type="checkbox"/> ALTER CASING <input type="checkbox"/> CHANGE TUBING <input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS <input type="checkbox"/> FRACTURE TREAT <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> RECLAMATION OF WELL SITE <input type="checkbox"/> SIDETRACK TO REPAIR WELL <input type="checkbox"/> VENT OR FLARE <input type="checkbox"/> SI TA STATUS EXTENSION <input type="checkbox"/> OTHER	<input type="checkbox"/> CASING REPAIR <input type="checkbox"/> CHANGE WELL NAME <input type="checkbox"/> CONVERT WELL TYPE <input type="checkbox"/> NEW CONSTRUCTION <input type="checkbox"/> PLUG BACK <input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION <input type="checkbox"/> TEMPORARY ABANDON <input type="checkbox"/> WATER DISPOSAL <input checked="" type="checkbox"/> APD EXTENSION OTHER: _____
<input type="checkbox"/> ACIDIZE <input type="checkbox"/> CHANGE TO PREVIOUS PLANS <input type="checkbox"/> CHANGE WELL STATUS <input type="checkbox"/> DEEPEN <input type="checkbox"/> OPERATOR CHANGE <input type="checkbox"/> PRODUCTION START OR RESUME <input type="checkbox"/> REPERFORATE CURRENT FORMATION <input type="checkbox"/> TUBING REPAIR <input type="checkbox"/> WATER SHUTOFF <input type="checkbox"/> WILDCAT WELL DETERMINATION	<input type="checkbox"/> ALTER CASING <input type="checkbox"/> CHANGE TUBING <input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS <input type="checkbox"/> FRACTURE TREAT <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> RECLAMATION OF WELL SITE <input type="checkbox"/> SIDETRACK TO REPAIR WELL <input type="checkbox"/> VENT OR FLARE <input type="checkbox"/> SI TA STATUS EXTENSION <input type="checkbox"/> OTHER	<input type="checkbox"/> CASING REPAIR <input type="checkbox"/> CHANGE WELL NAME <input type="checkbox"/> CONVERT WELL TYPE <input type="checkbox"/> NEW CONSTRUCTION <input type="checkbox"/> PLUG BACK <input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION <input type="checkbox"/> TEMPORARY ABANDON <input type="checkbox"/> WATER DISPOSAL <input checked="" type="checkbox"/> APD EXTENSION OTHER: _____			
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. Newfield proposes to extend the permit to drill this well for one year.					
Approved by the Utah Division of Oil, Gas and Mining					
Date: <u>April 21, 2010</u>					
By:					
NAME (PLEASE PRINT) Mandie Crozier	PHONE NUMBER 435 646-4825	TITLE Regulatory Tech			
SIGNATURE N/A	DATE 4/21/2010				

RECEIVED April 21, 2010



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43013342310000

API: 43013342310000

Well Name: STATE 4-36-8-15

Location: 0615 FNL 0468 FWL QTR NWNW SEC 36 TWNP 080S RNG 150E MER S

Company Permit Issued to: NEWFIELD PRODUCTION COMPANY

Date Original Permit Issued: 4/27/2009

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

- If located on private land, has the ownership changed, if so, has the surface agreement been updated? ☐ Yes ☒ No
- Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? ☐ Yes ☒ No
- Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well? ☐ Yes ☒ No
- Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? ☐ Yes ☒ No
- Has the approved source of water for drilling changed? ☐ Yes ☒ No
- Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? ☐ Yes ☒ No
- Is bonding still in place, which covers this proposed well? ☒ Yes ☐ No

**Approved by the
Utah Division of
Oil, Gas and Mining**

Signature: Mandie Crozier

Date: 4/21/2010

Title: Regulatory Tech **Representing:** NEWFIELD PRODUCTION COMPANY

Date: April 21, 2010

By: 

RECEIVED April 21, 2010

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING		FORM 9			
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.		5. LEASE DESIGNATION AND SERIAL NUMBER: ML-21835			
1. TYPE OF WELL Oil Well		6. IF INDIAN, ALLOTTEE OR TRIBE NAME:			
2. NAME OF OPERATOR: NEWFIELD PRODUCTION COMPANY		7. UNIT or CA AGREEMENT NAME: GMBU (GRRV)			
3. ADDRESS OF OPERATOR: Rt 3 Box 3630 , Myton, UT, 84052		8. WELL NAME and NUMBER: STATE 4-36-8-15			
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0615 FNL 0468 FWL QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: NWNW Section: 36 Township: 08.0S Range: 15.0E Meridian: S		9. API NUMBER: 43013342310000			
9. FIELD and POOL or WILDCAT: MONUMENT BUTTE		COUNTY: DUCHESNE			
STATE: UTAH					
11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA					
TYPE OF SUBMISSION	TYPE OF ACTION				
<input checked="" type="checkbox"/> NOTICE OF INTENT Approximate date work will start: 4/27/2011 <input type="checkbox"/> SUBSEQUENT REPORT Date of Work Completion: <input type="checkbox"/> SPUD REPORT Date of Spud: <input type="checkbox"/> DRILLING REPORT Report Date:	<table style="width: 100%; border: none;"> <tr> <td style="width: 33%; vertical-align: top;"> <input type="checkbox"/> ACIDIZE <input type="checkbox"/> CHANGE TO PREVIOUS PLANS <input type="checkbox"/> CHANGE WELL STATUS <input type="checkbox"/> DEEPEN <input type="checkbox"/> OPERATOR CHANGE <input type="checkbox"/> PRODUCTION START OR RESUME <input type="checkbox"/> REPERFORATE CURRENT FORMATION <input type="checkbox"/> TUBING REPAIR <input type="checkbox"/> WATER SHUTOFF <input type="checkbox"/> WILDCAT WELL DETERMINATION </td> <td style="width: 33%; vertical-align: top;"> <input type="checkbox"/> ALTER CASING <input type="checkbox"/> CHANGE TUBING <input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS <input type="checkbox"/> FRACTURE TREAT <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> RECLAMATION OF WELL SITE <input type="checkbox"/> SIDETRACK TO REPAIR WELL <input type="checkbox"/> VENT OR FLARE <input type="checkbox"/> SI TA STATUS EXTENSION <input type="checkbox"/> OTHER </td> <td style="width: 33%; vertical-align: top;"> <input type="checkbox"/> CASING REPAIR <input type="checkbox"/> CHANGE WELL NAME <input type="checkbox"/> CONVERT WELL TYPE <input type="checkbox"/> NEW CONSTRUCTION <input type="checkbox"/> PLUG BACK <input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION <input type="checkbox"/> TEMPORARY ABANDON <input type="checkbox"/> WATER DISPOSAL <input checked="" type="checkbox"/> APD EXTENSION OTHER: </td> </tr> </table>		<input type="checkbox"/> ACIDIZE <input type="checkbox"/> CHANGE TO PREVIOUS PLANS <input type="checkbox"/> CHANGE WELL STATUS <input type="checkbox"/> DEEPEN <input type="checkbox"/> OPERATOR CHANGE <input type="checkbox"/> PRODUCTION START OR RESUME <input type="checkbox"/> REPERFORATE CURRENT FORMATION <input type="checkbox"/> TUBING REPAIR <input type="checkbox"/> WATER SHUTOFF <input type="checkbox"/> WILDCAT WELL DETERMINATION	<input type="checkbox"/> ALTER CASING <input type="checkbox"/> CHANGE TUBING <input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS <input type="checkbox"/> FRACTURE TREAT <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> RECLAMATION OF WELL SITE <input type="checkbox"/> SIDETRACK TO REPAIR WELL <input type="checkbox"/> VENT OR FLARE <input type="checkbox"/> SI TA STATUS EXTENSION <input type="checkbox"/> OTHER	<input type="checkbox"/> CASING REPAIR <input type="checkbox"/> CHANGE WELL NAME <input type="checkbox"/> CONVERT WELL TYPE <input type="checkbox"/> NEW CONSTRUCTION <input type="checkbox"/> PLUG BACK <input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION <input type="checkbox"/> TEMPORARY ABANDON <input type="checkbox"/> WATER DISPOSAL <input checked="" type="checkbox"/> APD EXTENSION OTHER:
<input type="checkbox"/> ACIDIZE <input type="checkbox"/> CHANGE TO PREVIOUS PLANS <input type="checkbox"/> CHANGE WELL STATUS <input type="checkbox"/> DEEPEN <input type="checkbox"/> OPERATOR CHANGE <input type="checkbox"/> PRODUCTION START OR RESUME <input type="checkbox"/> REPERFORATE CURRENT FORMATION <input type="checkbox"/> TUBING REPAIR <input type="checkbox"/> WATER SHUTOFF <input type="checkbox"/> WILDCAT WELL DETERMINATION	<input type="checkbox"/> ALTER CASING <input type="checkbox"/> CHANGE TUBING <input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS <input type="checkbox"/> FRACTURE TREAT <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> RECLAMATION OF WELL SITE <input type="checkbox"/> SIDETRACK TO REPAIR WELL <input type="checkbox"/> VENT OR FLARE <input type="checkbox"/> SI TA STATUS EXTENSION <input type="checkbox"/> OTHER	<input type="checkbox"/> CASING REPAIR <input type="checkbox"/> CHANGE WELL NAME <input type="checkbox"/> CONVERT WELL TYPE <input type="checkbox"/> NEW CONSTRUCTION <input type="checkbox"/> PLUG BACK <input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION <input type="checkbox"/> TEMPORARY ABANDON <input type="checkbox"/> WATER DISPOSAL <input checked="" type="checkbox"/> APD EXTENSION OTHER: 			
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. Newfield requests to extend the Application for Permit to Drill this well for one year.					
<p style="color: red; font-weight: bold; margin: 0;">Approved by the Utah Division of Oil, Gas and Mining</p> <p style="color: red; font-weight: bold; margin: 0;">Date: 04/07/2011</p> <p style="color: red; font-weight: bold; margin: 0;">By: </p>					
NAME (PLEASE PRINT) Mandie Crozier		PHONE NUMBER 435 646-4825			
SIGNATURE N/A		TITLE Regulatory Tech			
DATE 4/4/2011					



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43013342310000

API: 43013342310000

Well Name: STATE 4-36-8-15

Location: 0615 FNL 0468 FWL QTR NWNW SEC 36 TWNP 080S RNG 150E MER S

Company Permit Issued to: NEWFIELD PRODUCTION COMPANY

Date Original Permit Issued: 4/27/2009

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

- If located on private land, has the ownership changed, if so, has the surface agreement been updated? ☐ Yes ☒ No
- Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? ☐ Yes ☒ No
- Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well? ☐ Yes ☒ No
- Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? ☐ Yes ☒ No
- Has the approved source of water for drilling changed? ☐ Yes ☒ No
- Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? ☐ Yes ☒ No
- Is bonding still in place, which covers this proposed well? ☒ Yes ☐ No

Signature: Mandie Crozier

Date: 4/4/2011

Title: Regulatory Tech **Representing:** NEWFIELD PRODUCTION COMPANY

RECEIVED Apr. 04, 2011

BLM - Vernal Field Office - Notification Form

Operator Newfield Exploration Rig Name/# Ross 21 Submitted By
Branden Arnold Phone Number 435-401-0223
Well Name/Number State 4-36-8-15
Qtr/Qtr NW/NW Section 36 Township 8S Range 15E
Lease Serial Number ML-21835
API Number 43-013-34231

Spud Notice – Spud is the initial spudding of the well, not drilling
out below a casing string.

Date/Time 4/27/11 9:00 AM ☒ PM ☐

Casing – Please report time casing run starts, not cementing
times.

- ☒ Surface Casing
- ☐ Intermediate Casing
- ☐ Production Casing
- ☐ Liner
- ☐ Other

Date/Time 4/27/11 3:00 AM ☐ PM ☒

BOPE

- ☐ Initial BOPE test at surface casing point
- ☐ BOPE test at intermediate casing point
- ☐ 30 day BOPE test
- ☐ Other

Date/Time _____ AM ☐ PM ☐

Remarks _____

STATE OF UTAH
DIVISION OF OIL, GAS AND MINING
ENTITY ACTION FORM -FORM 6

OPERATOR: NEWFIELD PRODUCTION COMPANY
ADDRESS: RT. 3 BOX 3630
MYTON, UT 84052

OPERATOR ACCT. NO. N2695

ACTION CODE	CURRENT ENTITY NO.	NEW ENTITY NO.	API NUMBER	WELL NAME	WELL LOCATION					SPUD DATE	EFFECTIVE DATE
					QQ	SC	TP	RG	COUNTY		
A	99999	18031	4301350446	BECKSTEAD 11-17-4-2W	NESW	17	4S	2W	DUCHESNE	4/26/2011	5/10/11
WELL 1 COMMENTS: GRRV											
B	99999	17400	4304751506	GMBU I-36-8-17	NWSE	36	8S	17E	UINTAH	5/6/2011	5/10/11
GRRV BHL = NENE											
B	99999	17400	4301350516	GMB N-22-8-17	SENW	22	8S	17E	DUCHESNE	4/23/2011	5/10/11
GRRV BHL = NWSW											
B	99999	17400	4301350515	GMB M-22-8-17	SENW	22	8S	17E	DUCHESNE	4/22/2011	5/10/11
GRRV BHL = NWSE											
B	99999	17400	4301334231	STATE 4-36-8-15	NWNW	36	8S	15E	DUCHESNE	4/27/2011	5/10/11
GRRV											
A	99999	18032	4304751130	UTE TRIBAL 13-20-4-2E	SWSW	20	4S	2E	UINTAH	4/29/2011	5/10/11
GRRV											

ACTION CODES (See instructions on back of form)

- A - new entity for new well (single well only)
- B - well to existing entity (group or unit well)
- C - from one existing entity to another existing entity
- D - well from one existing entity to a new entity
- E - other (explain in comments section)

NOTE: Use COMMENT section to explain why each Action Code was selected.

RECEIVED

MAY 09 2011

DIV. OF OIL, GAS & MINING

Signature

Jentri Park

Production Clerk

05/09/11

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

5. LEASE DESIGNATION AND SERIAL NUMBER:
UTAH STATE ML-21835

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7. UNIT or CA AGREEMENT NAME:
GMBU

1. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ OTHER

8. WELL NAME and NUMBER:
STATE 4-36-8-15

2. NAME OF OPERATOR:
NEWFIELD PRODUCTION COMPANY

9. API NUMBER:
4301334231

3. ADDRESS OF OPERATOR: Route 3 Box 3630 CITY Myton STATE UT ZIP 84052 PHONE NUMBER 435.646.3721

10. FIELD AND POOL, OR WILDCAT:
GREATER MB UNIT

4. LOCATION OF WELL:
FOOTAGES AT SURFACE: 06 15 FNL 0468 FWL

COUNTY: DUCHESNE

OTR/OTR. SECTION. TOWNSHIP. RANGE. MERIDIAN: NWNW, 36, T8S, R15E

STATE: UT

11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> NOTICE OF INTENT (Submit in Duplicate) Approximate date work will _____	<input type="checkbox"/> ACIDIZE	<input type="checkbox"/> DEEPEN	<input type="checkbox"/> REPERFORATE CURRENT FORMATION	
	<input type="checkbox"/> ALTER CASING	<input type="checkbox"/> FRACTURE TREAT	<input type="checkbox"/> SIDETRACK TO REPAIR WELL	
	<input type="checkbox"/> CASING REPAIR	<input type="checkbox"/> NEW CONSTRUCTION	<input type="checkbox"/> TEMPORARILY ABANDON	
	<input type="checkbox"/> CHANGE TO PREVIOUS PLANS	<input type="checkbox"/> OPERATOR CHANGE	<input type="checkbox"/> TUBING REPAIR	
	<input type="checkbox"/> CHANGE TUBING	<input type="checkbox"/> PLUG AND ABANDON	<input type="checkbox"/> VENT OR FLAIR	
<input checked="" type="checkbox"/> SUBSEQUENT REPORT (Submit Original Form Only) Date of Work Completion: 05/04/2011	<input type="checkbox"/> CHANGE WELL NAME	<input type="checkbox"/> PLUG BACK	<input type="checkbox"/> WATER DISPOSAL	
	<input type="checkbox"/> CHANGE WELL STATUS	<input type="checkbox"/> PRODUCTION (START/STOP)	<input type="checkbox"/> WATER SHUT-OFF	
	<input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS	<input type="checkbox"/> RECLAMATION OF WELL SITE	<input checked="" type="checkbox"/> OTHER: - Spud Notice	
	<input type="checkbox"/> CONVERT WELL TYPE	<input type="checkbox"/> RECOMPLETE - DIFFERENT FORMATION		

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

On 4/27/11 MIRU Ross #29. Spud well @12:00 AM. Drill 440' of 12 1/4" hole with air mist. TIH W/ 10 Jt's 8 5/8" J-55 24# csgn. Set @ 441.87. On 4/29/11 cement with 215 sks of class "G" w/ 2% CaCL2 + 0.25#/sk Cello- Flake Mixed @ 15.8ppg w/ 1.17ft3/sk yield. Returned 7 barrels cement to pit. WOC.

NAME (PLEASE PRINT) Branden Arnold

TITLE

SIGNATURE

DATE 05/05/2011

(This space for State use only)

RECEIVED

MAY 17 2011

DIV. OF OIL, GAS & MINING

NEWFIELD PRODUCTION COMPANY - CASING & CEMENT REPORT

8 5/8" CASING SET AT 441.87

LAST CASING	<u>14</u>	SET AT	<u>5</u>
DATUM	<u>12</u>		
DATUM TO CUT OFF CASING		<u>12</u>	
DATUM TO BRADENHEAD FLANGE		<u>12</u>	
TD DRILLER	<u>440</u>	LOGGER	<u></u>
HOLE SIZE	<u>12 1/4"</u>		

OPERATOR Newfield Exploration Company
WELL STATE 4-36-8-15
FIELD/PROSPECT Monument Butte
CONTRACTOR & RIG # Ross # 29

LOG OF CASING STRING:

PIECES	OD	ITEM - MAKE - DESCRIPTION		WT / FT	GRD	THREAD	CONDT	LENGTH
1		wellhead					A	1.42
10	8 5/8"	casing (shoe jt 40.30)		24	J-55	STC	A	429.55
1	8 5/8"	guide shoe					A	0.9
CASING INVENTORY BAL.		FEET	JTS	TOTAL LENGTH OF STRING				431.87
TOTAL LENGTH OF STRING		431.87	10	LESS CUT OFF PIECE				2
LESS NON CSG. ITEMS		2.32		PLUS DATUM TO T/CUT OFF CSG				12
PLUS FULL JTS. LEFT OUT		0		CASING SET DEPTH				441.87
TOTAL		429.55	10	} COMPARE				
TOTAL CSG. DEL. (W/O THRDS)								
TIMING								
BEGIN RUN CSG.	Spud	12:00 PM	4/27/2011	GOOD CIRC THRU JOB				Yes
CSG. IN HOLE		10:00 AM	4/28/2011	Bbls CMT CIRC TO SURFACE				
BEGIN CIRC		9:15 AM	4/29/2011	RECIPROCATED PIPI				No
BEGIN PUMP CMT		9:25 AM	4/29/2011	BUMPED PLUG TO				480
BEGIN DSPL. CMT		9:38 AM	4/29/2011					
PLUG DOWN		9:48 AM	4/29/2011					

[illegible]

COMPANY REPRESENTATIVE

Branden Arnold

DATE **5/4/2011**

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.

1. TYPE OF WELL: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NUMBER: UTAH STATE ML-21835
2. NAME OF OPERATOR: NEWFIELD PRODUCTION COMPANY		6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
3. ADDRESS OF OPERATOR: Route 3 Box 3630 CITY Myton STATE UT ZIP 84052		7. UNIT or CA AGREEMENT NAME: GMBU
PHONE NUMBER 435.646.3721		8. WELL NAME and NUMBER: STATE 4-36-8-15
4. LOCATION OF WELL: FOOTAGES AT SURFACE:		9. API NUMBER: 4301334231
OTR/OTR. SECTION. TOWNSHIP. RANGE. MERIDIAN: NWNW, 36, T8S, R15E		10. FIELD AND POOL, OR WILDCAT: GREATER MB UNIT
		COUNTY: DUCHESNE
		STATE: UT

11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION		
<input type="checkbox"/> NOTICE OF INTENT (Submit in Duplicate) Approximate date work will _____	<input type="checkbox"/> ACIDIZE	<input type="checkbox"/> DEEPEN	<input type="checkbox"/> REPERFORATE CURRENT FORMATION
	<input type="checkbox"/> ALTER CASING	<input type="checkbox"/> FRACTURE TREAT	<input type="checkbox"/> SIDETRACK TO REPAIR WELL
	<input type="checkbox"/> CASING REPAIR	<input type="checkbox"/> NEW CONSTRUCTION	<input type="checkbox"/> TEMPORARITLY ABANDON
	<input type="checkbox"/> CHANGE TO PREVIOUS PLANS	<input type="checkbox"/> OPERATOR CHANGE	<input type="checkbox"/> TUBING REPAIR
	<input type="checkbox"/> CHANGE TUBING	<input type="checkbox"/> PLUG AND ABANDON	<input type="checkbox"/> VENT OR FLAIR
<input checked="" type="checkbox"/> SUBSEQUENT REPORT (Submit Original Form Only) Date of Work Completion: 06/06/2011	<input type="checkbox"/> CHANGE WELL NAME	<input type="checkbox"/> PLUG BACK	<input type="checkbox"/> WATER DISPOSAL
	<input type="checkbox"/> CHANGE WELL STATUS	<input type="checkbox"/> PRODUCTION (START/STOP)	<input type="checkbox"/> WATER SHUT-OFF
	<input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS	<input type="checkbox"/> RECLAMATION OF WELL SITE	<input checked="" type="checkbox"/> OTHER: - Weekly Status Report
	<input type="checkbox"/> CONVERT WELL TYPE	<input type="checkbox"/> RECOMPLETE - DIFFERENT FORMATION	


12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

The above subject well was completed on 6/6/2011, attached is a daily completion status report.

RECEIVED

JUN 15 2011

DIV. OF OIL, GAS & MINING

NAME (PLEASE PRINT) Jennifer Peatross	TITLE Production Technician
SIGNATURE 	DATE 06/10/2011

(This space for State use only)

Daily Activity Report

Format For Sundry

STATE 4-36-8-15**4/1/2011 To 8/30/2011****5/23/2011 Day: 1****Completion**

Rigless on 5/23/2011 - Ran CBL & shot 1st stage - Install 5m frac head. NU 6" 5K Cameron BOP. RU H/O truck & pressure test casing, blind rams, frac head, csg & casing valves to 4500 psi. RU Perforators LLC WLT w/ mast & run CBL under pressure. WLTD @ 6191' & cement top @ 120'. Perforate stage #1, CP3 sds @ 5912-15' & CP1 sds @ 5798-5806' w/ 3 1/8" Port plug guns (11 gram .36" EH 16.82" pen) w/ 3 spf for total of 33 shots. 148 BWTR. SWIFN.

Daily Cost: \$0**Cumulative Cost:** \$9,738

5/26/2011 Day: 2**Completion**

Rigless on 5/26/2011 - Frac, perforate & flowback well as detailed. - Frac & perforate 5 stages as detailed. 2953 BWTR. Open for immediate flowback @ approx 3 BPM. Well flowed for 5 hours & died. Recovered approx 720 bbls. SWIFN. 2233 BWTR.

Daily Cost: \$0**Cumulative Cost:** \$161,680

5/27/2011 Day: 3**Completion**

NC #1 on 5/27/2011 - R/U NC#1, N/U Shafer BOP, RIH W/-Bit, 141 Jts Tbg, Drill Up Plgs @ 4400', 4940', Drill On Plg @ 5110' 2 Hrs, POOH W/2 Jts Tbg, SWI, C/SDFN. - 5:30AM-6:00AM C/Trvl, 6:00AM R/U NC#1, N/D 10,000 BOP, N/U 5,000 BOP, R/U R/Flr, Unload Tbg Off Float Onto Pipe Racks. P/U & RIH W/-4 3/4 Bit, Bit Sub, 140 Jts Tbg To Fill @ 4382', R/U R/pmp & RBS Pwr Swvl, Cln Out To Plg @ 4400', Drill Up Plg, 40 Min Drill Time. Swvl I/Hle To Fill @ 4862', Cln Out To Plg @ 4940', Drill Up Plg, 1 1/2 Hr Drill Time, Swvl I/Hle To Fill @ 5047', Cln Out To Plg @ 5110', Drill On Plg 2 Hrs, POOH W/-2 Jts Tbg EOB @ 5057', SWI, 6:30PM C/SDFN, 6:30PM-7:00PM C/Trvl. 2273 BWTR.

Daily Cost: \$0**Cumulative Cost:** \$169,658

5/31/2011 Day: 4**Completion**

NC #1 on 5/31/2011 - Continue Drilling Up Plg, @ 5110', RIH To Plg @ 5440', Drill Up Plg, Swvl I/Hle To Fill @ 6105', Cln Out To PBTD @ 6237', Curc Well Cln 1 Hr. POOH W/-4 Jts Tbg, EOB @ 6124'. SWI, C/SDFN. - 5:30AM-6:00AM C/Trvl, 6:00AM OWU, RIH W/-2 Jts Tbg To Plg @ 5110', Drill Up Plg, Swvl I/Hle To Plg @ 5440', Drill Up Plg 1 Hr 10 Min Drill Time, Swvl I/Hle To Fill @ 6105', Drill & Cln Out To PBTD @ 6237', Curc Well Cln 1 Hr, R/D Swvl, POOH W/-4 Jts Tbg, EOB @ 6124', SWI, 7:30PM C/SDFN, 7:30PM-8:00PM C/Trvl. 2322 BWTR.

Daily Cost: \$0**Cumulative Cost:** \$176,601

6/4/2011 Day: 5**Completion**

NC #1 on 6/4/2011 - Swab For Cln Up, Recvred 152 BW, 1% Oil Cut, FFL @ 900', RIH & Curc Out @ PBTD, POOH W/-Tbg & Bit. RIH W/-Tbg Production String. C/SDFN. - 5:30AM-6:00AM

C/Trvl, 6:00AM OWU, RIH W/-Swab, IFL @ 300', Made 15 Swab Runs, Recvred 152 BW, 1% Oil Cut, FFL @ 900'. R/D Swab. RIH W/-4 Jts Tbg To Fill @ 6225', R/U R/pmp, Cln Out To PBTD @ 6237', Curc Well Cln. POOH W/-199 Jts Tbg, Bit Sub & Bit. P/U & RIH W/-N/C, 1 Jt Tbg, S/N, 1 Jt Tbg, 5 1/2" T/A, 187 Jts Tbg, SWI, 5:00PM C/SDFN, 5:00PM-5:30PM C/Trvl. 2262 BWTR.

Daily Cost: \$0

Cumulative Cost: \$183,331

6/6/2011 Day: 6**Completion**

NC #1 on 6/6/2011 - Set T/A,N/U W/HD.Run pmp & Rod Production Strng,R/U Unit, Fill & Tst Tbg To 800 Psi, Good Test.R/D Rig, POP. (Final Report). - 5:30AM-6:00AM C/Trvl, 6:00AM OWU, R/D R/Flr, N/D BOP, Set T/A In 18,000 Tension, N/U W/-HD. P/U Stroke & RIH W/- Central Hyd 2 2/1X1 1/2X20X24' RHAC, 1"X4' 3 Per Stabilizer Pony, 6- 1 1/2 Wt Bars, 127- 3/4 4 Per, 101-7/8 4 Per, 7/8X8'-6'-4'-2' Ponys, 1 1/2X26' Polish Rod, Seat pmp, R/U Unit, R/U R/pmp, Fill Tbg W/-2 BW, Stroke Unit & Tbg To 800 Psi, Good Test. Rack Out Eq, R/D Rig, POP @ 3:30PM , 122" SL, 5 SPM, 2264 BWTR,3:30PM -4:00PM C/Trvl (Final Report).

Finalized

Daily Cost: \$0

Cumulative Cost: \$252,146

Pertinent Files: Go to File List

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0137
Expires: July 31, 2010

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well ☒ Oil Well ☐ Gas Well ☐ Dry ☐ Other
b. Type of Completion: ☒ New Well ☐ Work Over ☐ Deepen ☐ Plug Back ☐ Diff. Resvr.,
Other: _____

2. Name of Operator
NEWFIELD EXPLORATION COMPANY

3. Address
1401 17TH ST. SUITE 1000 DENVER, CO 80202

3a. Phone No. (include area code)
(435) 646-3721

4. Location of Well (Report location clearly and in accordance with Federal requirements)*

At surface 615' FNL & 468' FWL (NW/NW) SEC. 36, T9S, R15E

At top prod. interval reported below

At total depth 6280'

14. Date Spudded
04/27/2011

15. Date T.D. Reached
05/16/2011

16. Date Completed 06/06/2011
☐ D & A ☒ Ready to Prod.

18. Total Depth: MD 6280'
TVD

19. Plug Back T.D.: MD 6237'
TVD

20. Depth Bridge Plug Set: MD
TVD

21. Type Electric & Other Mechanical Logs Run (Submit copy of each)

☒ DUAL IND GRD, SP, COMP. DENSITY, COMP. NEUTRON, GR, CALIPER, CMT BOND

22. Was well cored? ☒ No ☐ Yes (Submit analysis)
Was DST run? ☒ No ☐ Yes (Submit report)
Directional Survey? ☒ No ☐ Yes (Submit copy)

23. Casing and Liner Record (Report all strings set in well)

Hole Size	Size/Grade	Wt. (#/ft.)	Top (MD)	Bottom (MD)	Stage Cement Depth	No. of Sks. & Type of Cement	Slurry Vol. (BBL)	Cement Top*	Amount Pulled
12-1/4"	8-5/8" J-55	24#	0	440'		215 CLASS G			
7-7/8"	5-1/2" J-55	15.5#	0	6283'		300 PRIMLITE		120'	
						400 50/50 POZ			

24. Tubing Record

Size	Depth Set (MD)	Packer Depth (MD)	Size	Depth Set (MD)	Packer Depth (MD)	Size	Depth Set (MD)	Packer Depth (MD)
2-7/8"	EOT@ 5946'	TA @ 5879'						

25. Producing Intervals

Formation	Top	Bottom	Perforated Interval	Size	No. Holes	Perf. Status
A) Green River	4319'	5915'	4319-5915'	.36"	162	
B)						
C)						
D)						

27. Acid, Fracture, Treatment, Cement Squeeze, etc.

Depth Interval	Amount and Type of Material
4319-5915'	Frac w/ 357758#s 20/40 sand in 2266 bbls of Lightning 17 fluid in 5 stages.

28. Production - Interval A

Date First Produced	Test Date	Hours Tested	Test Production	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method
6/7/11	6/17/11	24	→	241	0	50			2-1/2" x 1-1/2" x 20' x 24' RHAC Pump
Choke Size	Tbg. Press. Flwg. SI	Csg. Press.	24 Hr. Rate	Oil BBL	Gas MCF	Water BBL	Gas/Oil Ratio	Well Status	
			→					PRODUCING	

28a. Production - Interval B

Date First Produced	Test Date	Hours Tested	Test Production	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method
			→						
Choke Size	Tbg. Press. Flwg. SI	Csg. Press.	24 Hr. Rate	Oil BBL	Gas MCF	Water BBL	Gas/Oil Ratio	Well Status	
			→						

*(See instructions and spaces for additional data on page 2)

RECEIVED
JUL 12 2011

DIV. OF OIL, GAS & MINING

28b. Production - Interval C

Date First Produced	Test Date	Hours Tested	Test Production →	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method
Choke Size	Tbg. Press. Flwg. SI	Csg. Press.	24 Hr. Rate →	Oil BBL	Gas MCF	Water BBL	Gas/Oil Ratio	Well Status	

28c. Production - Interval D

Date First Produced	Test Date	Hours Tested	Test Production →	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method
Choke Size	Tbg. Press. Flwg. SI	Csg. Press.	24 Hr. Rate →	Oil BBL	Gas MCF	Water BBL	Gas/Oil Ratio	Well Status	

29. Disposition of Gas (Solid, used for fuel, vented, etc.)

USED FOR FUEL

30. Summary of Porous Zones (Include Aquifers):

Show all important zones of porosity and contents thereof: Cored intervals and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures and recoveries.

31. Formation (Log) Markers

GEOLOGICAL MARKERS

Formation	Top	Bottom	Descriptions, Contents, etc.	Name	Top
					Meas. Depth
GREEN RIVER	4319'	5915'		GARDEN GULCH MRK GARDEN GULCH 1	3806' 4036'
				GARDEN GULCH 2 POINT 3	4153' 4426'
				X MRKR Y MRKR	4689' 4727'
				DOUGLAS CREEK MRK BI CARBONATE MRK	4839' 5096'
				B LIMESTONE MRK CASTLE PEAK	5221' 5735'
				BASAL CARBONATE	6159'

32. Additional remarks (include plugging procedure):

33. Indicate which items have been attached by placing a check in the appropriate boxes:

- ☐ Electrical/Mechanical Logs (1 full set req'd.)
 ☐ Geologic Report
 ☐ DST Report
 ☐ Directional Survey
☐ Sundry Notice for plugging and cement verification
 ☐ Core Analysis
☒ Other: Drilling Daily Activity

34. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records (see attached instructions)*

Name (please print) Jennifer Peatross

Title Production Technician

Signature

Date 07/05/2011

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 3)

(Form 3160-4, page 2)

Daily Activity Report**Format For Sundry****STATE 4-36-8-15****3/1/2011 To 7/30/2011****STATE 4-36-8-15****Waiting on Cement****Date:** 5/4/2011

Ross #29 at 440. Days Since Spud - @ 441.87'KB. On 4/29/11 cement w/BJ w/215 sks of class G+2%kcl+.25#CF mixed @ 15.8ppg and 1.17 - yield. Returned 7bbls to pit, bump plug to 480psi, BLM and State were notified of spud via email. - On 4/27/11 Ross #29 spud and drilled 440' of 12 1/4" hole, P/U and run 10 jts of 8 5/8" casing set

Daily Cost: \$0**Cumulative Cost:** \$76,233

STATE 4-36-8-15**Drill 7 7/8" hole with fresh water****Date:** 5/13/2011

NDSI #2 at 1910. 1 Days Since Spud - Drill 7-7/8" hole from 380' to 1910' with 20,000 lbs WOB, 138 total RPM, 400 GPM 161 fph avg ROP - 4:00 PM. - 24 hr notice sent to State via email of rig move on 5/12/2011 @ 12:00 pm and BOP test on 5/12/2011 @ - and valve. Inside Valves and manifold 2000 psi for ten minutes. Then the surface casing at 1500 psi - for 30 min. All tests ok - On 5/13/2011 MIRU set equipment w/ Liddell Trucking (5 mile rig move from the UT 3-27-4-3W) - 3.39', 6-6" drill collars 239.56'. Tag cement at 380' - Pick BHA as follows; Smith Mi 616 PDC bit, Hunting 3.8 stage mud motor 26.84', NMDC 31.08', Gap sub - Accept rig at 1600 on 5/13/2011. R/U B&C Quicktest. Test Kelly, pipe rams, blind rams, choke line

Daily Cost: \$0**Cumulative Cost:** \$99,394

STATE 4-36-8-15**Drill 7 7/8" hole with fresh water****Date:** 5/14/2011

NDSI #2 at 4185. 2 Days Since Spud - Drill 7-7/8" hole from 1910' to 2929' with 20,000 lbs WOB, 138 total RPM, 400 GPM 145 fph avg ROP - Rig service - Circulate - Trip out of hole. For pressure loss - Lay down mud motor and pick up new bit. - Trip in hole - Drill 7-7/8" hole from 2929' to 4185' with 20,000 lbs WOB, 138 total RPM, 400 GPM 145 fph avg ROP

Daily Cost: \$0**Cumulative Cost:** \$149,561

STATE 4-36-8-15**Drill 7 7/8" hole with fresh water****Date:** 5/15/2011

NDSI #2 at 5800. 3 Days Since Spud - Rig repair. Replace low chain in drawworks - Drill 7-7/8" hole from 4829' to 5685' with 20,000 lbs WOB, 138 total RPM, 400 GPM 63.4 fph avg ROP - Rig service. Function test Bop and crown-o-matic - Drill 7-7/8" hole from 4185' to 4829' with 20,000 lbs WOB, 138 total RPM, 400 GPM 107.33 fph avg ROP - Drill 7-7/8" hole from 5685' to 5800' with 20,000 lbs WOB, 138 total RPM, 400 GPM 46 fph avg ROP

Daily Cost: \$0**Cumulative Cost:** \$171,250

STATE 4-36-8-15**Circulate & Condition Hole****Date:** 5/16/2011

NDSI #2 at 6280. 4 Days Since Spud - R/U casing crew and run 149 jts of 5 1/2" 15.50# J55 casing set at 6289'/KB. Land casing mandrill - with 70,000# tension - Circulate and rig up BJ

hard lines - Pressure test BJ lines and start the fresh water spacers. - Pump 300 sks lead cement PL11+3%KCL+5#CSE+.5#CF+5#KOL+.5SMS+FP+SF mixed at 11ppg 3.43 yield. - Then 400 sacks tail 50:50:2+3%KCL+.5%EC-1+.25#CF+.05#SF+.3SMS+FP-6L. Mixed at 14.4ppg 1.24 yield - Clean mud tanks. Release rig at 1130 5/16/2011 - Test casing rams to 2000 psi for ten minutes. Test good - R/U PSI and log well with tripple combo suite - Lay down BHA - Wait on loggers - Lay down pipe to the BHA - Pump 260 bbls of 10# brine - Lay down DP to 4000'. Well flowing at 11 gal/min - Circulate - Drill 7-7/8" hole from 5800' to 6280' with 20,000 lbs WOB, 138 total RPM, 400 GPM 80 fph avg ROP - Clean mud tanks. Release rig at 1130 5/16/2011 - Then 400 sacks tail 50:50:2+3%KCL+.5%EC-1+.25#CF+.05#SF+.3SMS+FP-6L. Mixed at 14.4ppg 1.24 yield - Pump 300 sks lead cement PL11+3%KCL+5#CSE+.5#CF+5#KOL+.5SMS+FP+SF mixed at 11ppg 3.43 yield. - Pressure test BJ lines and start the fresh water spacers. - Circulate and rig up BJ hard lines - with 70,000# tension - R/U casing crew and run 149 jts of 5 1/2" 15.50# J55 casing set at 6289'/KB. Land casing mandrill - Test casing rams to 2000 psi for ten minutes. Test good - R/U PSI and log well with tripple combo suite - Lay down BHA - Wait on loggers - Lay down pipe to the BHA - Pump 260 bbls of 10# brine - Lay down DP to 4000'. Well flowing at 11 gal/min - Drill 7-7/8" hole from 5800' to 6280' with 20,000 lbs WOB, 138 total RPM, 400 GPM 80 fph avg ROP - Circulate **Finalized**

Daily Cost: \$0

Cumulative Cost: \$306,920

Pertinent Files: Go to File List



GARY R. HERBERT
Governor

SPENCER J. COX
Lieutenant Governor

State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER
Executive Director

Division of Oil, Gas and Mining

JOHN R. BAZA
Division Director

November 28, 2016

CERTIFIED MAIL NO.: 7015 0640 0003 5276 0440

Mr. Kirby Carroll
Newfield Production Company
1001 17th Street, STE 2000
Denver, CO 80202

43 013 34231
state 4-36-8-15
36 8S 15E

Subject: Extended Shut-in and Temporary Abandoned Well Requirements for Fee or State Leases

Dear Mr. Carroll:

As of August 2016, Newfield has thirty-two (32) State and Fee Lease Wells (see attachment A) that are currently in non-compliance with the requirements for extended shut-in or temporarily abandoned (SI/TA) status.

Wells SI/TA beyond twelve (12) consecutive months requires filing a Sundry Notice (R649-3-36-1). Wells with five (5) years non-activity or non-productivity shall be plugged, unless the Division grants approval for extended shut-in time upon a showing of good cause by the operator (649-3-36-1.3.3). For extended SI/TA consideration the operator shall provide the Utah Division of Oil, Gas and Mining with the following:

1. Reasons for SI/TA of the well (R649-3-36-1.1).
2. The length of time the well is expected to be SI/TA (R649-3-36-1.2), and
3. An explanation and supporting data if necessary, for showing the well has integrity, meaning that the casing, cement, equipment condition, static fluid level, pressure, existence or absence of Underground Sources of Drinking Water and other factors do not make the well a risk to public health and safety or the environment (R649-3-36-1.3).

Please note that the Divisions preferred method for showing well integrity is by MIT.

Page 2
Newfield Production Company
November 28, 2016


Submitting the information suggested below may help show well integrity and may help qualify your well for extended SI/TA. **Note: As of July 1, 2003, wells in violation of the SI/TA rule R649-3-36 may be subject to full cost bonding (R649-3-1-4.2, 4.3).**

1. Wellbore diagram, and
2. Copy of recent casing pressure test, and
3. Current pressures on the wellbore (tubing pressure, casing pressure, and casing/casing annuli pressure) showing wellbore has integrity, and
4. Fluid level in the wellbore, and
5. An explanation of how the submitted information proves integrity.

All Submittals should be sent via ePermit

If the required information is not received within 30 days of the date of this notice, further actions may be initiated. If you have any questions concerning this matter, please contact me at (801) 538-5281.

Sincerely,



Dustin K. Doucet
Petroleum Engineer

DKD/DD/js

cc: Compliance File
Well File
LaVonne Garrison, SITLA

N:\O&G Reviewed Docs\ChronFile\PetroleumEngineer\SITA

ATTACHMENT A

	Well Name	API	LEASE	Years.Months Inactive
1	GMBU 2-16-9-18H	43-047-52013	ML-48378	4.4
2	Gulf State 36-13	43-047-31345	ML-22057	9.2
3	Moon 3-20-4-2	43-013-50007	Fee	3.5
4	S Mon Butte ST P-2-9-16	43-013-50118	ML-21839	3.6
5	State 3-16-9-18	43-047-35813	ML-48378	3.5
6	Wells Draw ST 7-36	43-013-30934	ML-21835	3.4
7	Prewitt 10-24	43-013-31865	Fee	3.2
8	W Draw ST N-32-8-16	43-013-34146	ML-45555	2.4
9	Wells Draw 2-32-8-16	43-013-32220	ML-21836	2.3
10	GMBU N-2-9-15	43-013-50910	ML-43538	2.2
11	GMBU M-2-9-15	43-013-50909	ML-43538	2.1
12	Moon 1-29-4-2	43-013-50006	Fee	2.0
13	Moon 1-20-4-2	43-013-50008	Fee	2.0
14	State 1-36-8-15	43-013-34234	ML-21835	2.5
15	Ashley ST 6-2-9-15	43-013-32584	ML-43538	1.10
16	Allen Trust 2-24	43-013-31944	Fee	1.9
17	Lamb 4-34-4-1E	43-047-40272	Fee	1.5
18	Wells Draw 4-32-8-16	43-013-32222	ML-21836	1.8
19	Greater Mon Butte T-36-8-16	43-013-50211	ML-22061	1.8
20	Williams #14-8-4-2	43-013-50617	Fee	1.8
21	Hancock 11-21-4-1	43-013-33242	Fee	1.5
22	Malnar 9-19-4-1	43-013-33913	Fee	1.2
23	Hancock 16-20-4-1	43-013-33914	Fee	1.0
24	State 12-36-8-15	43-013-34224	ML-21835	2.1
→ 25	State 4-36-8-15	43-013-34231	ML-21835	1.4
26	Roberts 4-19-4-1	43-013-50072	Fee	1.1
27	Mon Butte East K-36-8-16	43-013-50112	ML-22061	1.1
28	S Mon Butte ST N-2-9-16	43-013-50117	ML-21839	1.4
29	Wilcken 16-23-4-2	43-013-50304	Fee	1.0
30	Hancock 12-7-4-1W	43-013-50422	Fee	1.3
31	State 1-16-9-18	43-047-35811	ML-48378	1.6
32	Lamb 1-34-4-1E	43-047-40275	Fee	1.1



GARY R. HERBERT
Governor

SPENCER J. COX
Lieutenant Governor

State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER
Executive Director

Division of Oil, Gas and Mining

JOHN R. BAZA
Division Director

December 14, 2016

CERTIFIED MAIL NO.: 7015 0640 0003 5276 0525

Ms. Assiya Bekniyazova
Newfield Production Company
4 Waterway Square PL, STE 100
The Woodlands, TX 77380

43 013 3A 231
State 4-36-8-15
36 8S 15E

Subject: Extended Shut-in and Temporary Abandoned Well Requirements for Fee or State Leases

Dear Ms. Bekniyazova:

As of August 2016, Newfield has thirty-two (32) State and Fee Lease Wells (see attachment A) that are currently in non-compliance with the requirements for extended shut-in or temporarily abandoned (SI/TA) status.

Wells SI/TA beyond twelve (12) consecutive months requires filing a Sundry Notice (R649-3-36-1). Wells with five (5) years non-activity or non-productivity shall be plugged, unless the Division grants approval for extended shut-in time upon a showing of good cause by the operator (649-3-36-1.3.3). For extended SI/TA consideration the operator shall provide the Utah Division of Oil, Gas and Mining with the following:

1. Reasons for SI/TA of the well (R649-3-36-1.1).
2. The length of time the well is expected to be SI/TA (R649-3-36-1.2), and
3. An explanation and supporting data if necessary, for showing the well has integrity, meaning that the casing, cement, equipment condition, static fluid level, pressure, existence or absence of Underground Sources of Drinking Water and other factors do not make the well a risk to public health and safety or the environment (R649-3-36-1.3).

Please note that the Divisions preferred method for showing well integrity is by MIT.



Page 2
Newfield
December 14, 2016


Submitting the information suggested below may help show well integrity and may help qualify your well for extended SI/TA. **Note: As of July 1, 2003, wells in violation of the SI/TA rule R649-3-36 may be subject to full cost bonding (R649-3-1-4.2, 4.3).**

1. Wellbore diagram, and
2. Copy of recent casing pressure test, and
3. Current pressures on the wellbore (tubing pressure, casing pressure, and casing/casing annuli pressure) showing wellbore has integrity, and
4. Fluid level in the wellbore, and
5. An explanation of how the submitted information proves integrity.

All Submittals should be sent via ePermit

If the required information is not received within 30 days of the date of this notice, further actions may be initiated. If you have any questions concerning this matter, please contact me at (801) 538-5281.

Sincerely,



Dustin K. Doucet
Petroleum Engineer

DKD/DD/js

cc: Compliance File
Well File
LaVonne Garrison, SITLA

N:\O&G Reviewed Docs\ChronFile\PetroleumEngineer\SITA

ATTACHMENT A

	Well Name	API	LEASE	Years.Months Inactive
1	GMBU 2-16-9-18H	43-047-52013	ML-48378	4.4
2	Gulf State 36-13	43-047-31345	ML-22057	9.2
3	Moon 3-20-4-2	43-013-50007	Fee	3.5
4	S Mon Butte ST P-2-9-16	43-013-50118	ML-21839	3.6
5	State 3-16-9-18	43-047-35813	ML-48378	3.5
6	Wells Draw ST 7-36	43-013-30934	ML-21835	3.4
7	Prewitt 10-24	43-013-31865	Fee	3.2
8	W Draw ST N-32-8-16	43-013-34146	ML-45555	2.4
9	Wells Draw 2-32-8-16	43-013-32220	ML-21836	2.3
10	GMBU N-2-9-15	43-013-50910	ML-43538	2.2
11	GMBU M-2-9-15	43-013-50909	ML-43538	2.1
12	Moon 1-29-4-2	43-013-50006	Fee	2.0
13	Moon 1-20-4-2	43-013-50008	Fee	2.0
14	State 1-36-8-15	43-013-34234	ML-21835	2.5
15	Ashley ST 6-2-9-15	43-013-32584	ML-43538	1.10
16	Allen Trust 2-24	43-013-31944	Fee	1.9
17	Lamb 4-34-4-1E	43-047-40272	Fee	1.5
18	Wells Draw 4-32-8-16	43-013-32222	ML-21836	1.8
19	Greater Mon Butte T-36-8-16	43-013-50211	ML-22061	1.8
20	Williams #14-8-4-2	43-013-50617	Fee	1.8
21	Hancock 11-21-4-1	43-013-33242	Fee	1.5
22	Malnar 9-19-4-1	43-013-33913	Fee	1.2
23	Hancock 16-20-4-1	43-013-33914	Fee	1.0
24	State 12-36-8-15	43-013-34224	ML-21835	2.1
→ 25	State 4-36-8-15	43-013-34231	ML-21835	1.4
26	Roberts 4-19-4-1	43-013-50072	Fee	1.1
27	Mon Butte East K-36-8-16	43-013-50112	ML-22061	1.1
28	S Mon Butte ST N-2-9-16	43-013-50117	ML-21839	1.4
29	Wilcken 16-23-4-2	43-013-50304	Fee	1.0
30	Hancock 12-7-4-1W	43-013-50422	Fee	1.3
31	State 1-16-9-18	43-047-35811	ML-48378	1.6
32	Lamb 1-34-4-1E	43-047-40275	Fee	1.1